

SERIES 77 Lipped, Straight Shrink Boots 770-018S Commercial Heavy Wall Boot



How to Order



Lipped, heavy wall straight heat shrink boots provide mechanical and environmental protection from damage and debris. These heavy wall shrink boots are the commercial equivalent to our 770-008S NAVSEA qualified boots and are available in all eight materials and all five adhesive choices. Glenair straight boots fit most standard boot adapters for circular connectors. All adhesive lined and unlined shrink books are RoHS compliant. Shrink boots are water-tight when equipped with factory installed or user-installed adhesive. Lipped boots lock into boot groove located on adapter. Choose boot size based on adapter diameter and cable diameter.

How to Order									
Sample Part Number	770	-018	S	1	03	W1			
Product Series	770 = Series 77 shrink boot								
Basic Number	018 = heavy wall lipped boot								
Angular Function	S = straight								
Material	See material and adhesives table								
Boot Size	00, 01, 02, 03, 04, 05; see dimensions table					-			
Adhesive Lined	Omit for no adhesive; see material and adhesives table						-		

Material and Adhesive Compatibility								
Material Code	Material Description (Compound No.)		Hot Melt Adhesives	High Performance Epoxy Adhesives				
		W1	W2	W3 (TACOM approved)	R	U		
		High Temperature -55°C to 125°C	Standard -55°C to 70°C	Elastomeric -55°C to 125°C	Pre-Coat -75°C to 150°C	Two-Part -75°C to 155°C		
1	High-Performance Semi-Rigid Elastomer (2025)	•	•		•	Tunallanava		
2	Zero Halogen Semi-Rigid Polyolefin (2010)	•	•		•	Type U epoxy adhesive is		
3	General Purpose Flexible Polyolefin (2040)		•			compatible with all		
5	Viton Fluoroelastomer Blend (2050)	•		•	•	boot materials.		
6	High Performance Elastomer Alloy (2051)	•		•		Ordered separately, user-installed		
7	Semi-Rigid Polyolefin (2071)	•	•			(779-001). Order		
8	Low Outgassing Fluoropolymer Alloy (2008)	Material Type 8 not	boot with no					
9	Low Temp Flexible Polyolefin (2013)		•			adhesive lining.		

NOTES

1. See Modification Codes listed in Section A for material color options available for Type 1 (compound 2025) material.




Lipped, Straight Shrink Boots 770-018S Commercial Heavy Wall Boot



Lipped Straight Adapter Shrink Boots, Standard: Dimensions

Dimensions




	Dimensions								
Boot Size	Glenair Part Marking	AS858049/140 Fig 4 Reg	Ae Dia. Min Expanded	Ar Dia Max Recovered	Ce Dia. Min Expanded	Cr Dia. Max Recovered	PO ±10%	R ±10%	
00	S00	23	.827 (21.0)	.551 (14.0)	.630 (16.0)	.209 (5.3)	5.315 (135.0)	1.10 (27.9)	
01	S01	24	.984 (25.0)	.650 (16.5)	.984 (25.0)	.331 (8.4)	6.024 (153.0)	1.20 (30.5)	
02	S02	25	1.299 (33.0)	.799 (20.3)	1.299 (33.0)	.429 (10.9)	6.024 (153.0)	1.20 (30.5)	
03	S03	26	1.693 (43.0)	.902 (22.9)	1.693 (43.0)	.559 (14.2)	6.890 (175.0)	1.50 (38.1)	
04	S04	27	2.087 (53.0)	1.098 (27.9)	2.087 (53.0)	.701 (17.8)	6.890 (175.0)	1.50 (38.1)	
05	S05	28	2.835 (72.0)	1.449 (36.8)	2.835 (72.0)	.949 (24.1)	7.244 (184.0)	1.60 (40.6)	

For materials Type 2, Type 3 and Type 9, dimension 'Ce' is nominal

Lipped Straight Shrink Boots: Part Marking, Raised Lettering

EXPANDED RECOVERED



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

5685710001 CR9960-000 5734012004 607381P039 611112-000 6284592002 CX4711-000 CZ1420-000 D-306-38 770-006S302 770-010Y106W1 770-018S103 770-018S202W1 770-018S205W1 770-020S704W1 770-020S705 MFP-1/4"-Clear MFP-3/64"-Clear 790-3012 MHHT-4-15K2-G-104 8003012003 MIL-LT-1-1/2-4-SP MIL-LT-1-1/2-9-STK MIL-LT-1/2-2-STK MIL-LT-3-0-SP MIL-LT-3/32-0-SP MIL-LT-3/32-6-SP MIL-LT-3/4-4-STK MIL-LT-3/4-6-SP 839602-000 8423-6 FP301-116-48"-Clear FP301-12-6"-Clear FP301-1/4-48"-White-Hdr FP301-18-48"-Black-Hdr FP301-1/8-6"-Black FP301-18-6"-Black-Bulk FP301-316-48"-Blue-Hdr FP301-34-48"-Green-Hdr 912229N002 R280637030 HDT-0300-48A-BLACK HDT-0400-48A-Black HDT-0800-48A-RED HDT1100-48A-BLK HDT1500-48A-BLK HDT-2000-48A-Black RHW-70/20-1200/ADH-0 DWP-125-0.450-4-55MM-CS879 156082-000