## **Series 80 Mighty Mouse Contacts and Tools**

# Contact Insertion and Removal Tools and Contact Retention Tester

#### **Contact insertion and removal tools**



Figure	Size	Туре	Part Number	Military Part Number	Daniels Part Number
1	#23	Insertion/Extraction	809-088	(None)	(None)
2	#23	Insertion Only	809-013	(None)	DAK225-22
3	#20HD	Insertion/Extraction	809-203 (Append D for Delrin tip)	(None)	(None)
4	#16	Insertion/Extraction	809-131	M81969/14-03	(None)
5	#12	Insertion/extraction	<b>809-132</b> M81969/14-04		(None)
6	#20	Insertion/extraction	809-207	M81969/14-10	(None)

Insertion/Extraction Tool for #23 Contacts. Features molded plastic grips and sturdy stainless steel tips. Blue/White molded handle.

2 Insertion Tool for #23 Contacts. This tool features anodized aluminum handle and stainless steel insertion tip.

Insertion/Extraction Tool for #20HD Contacts.
This tool features molded plastic grips and sturdy stainless steel or Delrin tips. Molded handle in Green/White for SS or Green/Blue for Delrin tips.

4 Insertion/Extraction Tool for #16 Contacts. Use with size #16 coaxial or power contacts. Economical molded plastic. White extraction tip, blue insertion tip.

Insertion/Extraction Tool for #12 Contacts.
Use with size #12 coaxial or power contacts.
Molded plastic. White extraction tip, yellow insertion tip.

6 Insertion/Extraction Tool for #20 Contacts.
Molded plastic. Orange extraction tip, red insertion tip.

## Contact retention testers for size #23, #20, #16, #12 contacts (Kit or Individual Parts)



Check for properly seated contacts with this spring-loaded tester. Apply the tool tip to the mating end of a contact. Push on the handle until the spring compresses to the recommended force. A visual indicator shows full compression. The contact is properly retained if it is not displaced.

Adjust handle to appropriate settings:

Contact	P/N	Setting
#23	809-107-1	3.2 pounds
#20 & 20HD	809-370-1	8 pounds
#16	809-371-1	13 pounds
#12	809-372-1	13 pounds

Contact Size	Handle	Pin Tip	Socket Tip	Complete Kit
#23	809-107-1 (HT250-2)	809-107-2 (68-023-01)	809-107-3 (67-023-01)	809-107-4
#20 & 20HD	809-370-1 (HT250-4)	890-370-2 (68-020-01)	809-370-3 (67-020-01)	809-370-4
#16	809-371-1 (HT250-4)	809-371-2 (68-016-01)	809-371-3 (67-016-01)	809-371-4
#12	809-372-1 (HT250-4)	809-372-2 (68-012-01)	809-372-3 (67-012-01)	809-372-4

Daniels part numbers provided in parethesis

Dimensions in Inches (millimeters) are subject to change without notice.

© 2014 Glenair, Inc. Series 80 Mighty Mouse U.S. CAGE Code 06324

Printed in U.S.A.

GLENAIR, INC. • 1211 AIR WAY • GLENDALE, CA 91201-2497 • 818-247-6000 • FAX 818-500-9912 www.glenair.com

A-14

E-Mail: sales@glenair.com

Rev. 12.11.19

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Extraction, Removal & Insertion Tools category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

M8196914-08 768211-2 809-131 844751-2 8-59558-2 91018-1 12014013 12093647 1-21048-0 R282867020 12093078 12180559 121048-6 12121897 DCF.91.405.5LT 1322 13549852 15314260 15313892 15350698 15350707 15430130 1643916-1 1-679532-0
1976593-3 OUTEXT-0321 2-1579008-3 2-1579008-4 229694-7 231106-1 241469 91040-3 91040-7 965004-000 965069-000 1738219-1
ET-JL05-16 FG 0300 146 3000 FIT-6 210S048 2-1579007-9 231879-1 CF-008025-000 312138-3 RJ11FODE 356-162 M8196914-10 41579018-0 483249-1 5-1579007-2