Series 80 Mighty Mouse Contacts and Tools

Coaxial Contacts




Size #16 coaxial contacts


These #16 contacts accept 50 ohm and 75 ohm coaxial cable. Inner contact is rated at 1 amp, the outer contact 12 amps. DWV voltage rating is 800 Vac rms sea level, 250 Vac at 50,000 feet. Contacts are packaged individually and are unassembled with instruction sheet. One contact consists of outer contact, fluorocarbon dielectric, inner contact and shield crimp sleeve. Inner and outer contacts are gold-plated copper alloy. Approved to SAE AS39029. VSWR rating 1.5:1 maximum up to 700 MHz. 5000 megohm insulation resistance.



| Туре | Cable Size | Part Number | Military Part Number | Color Band | | | Tool Code |
|--------|---------------------|----------------|-------------------------|------------|--------|--------|------------|
| | | | | 1st | 2nd | 3rd | 1001 Code |
| Pin | RG174, RG316, RG179 | 809-114 | M39029/76-424 | Yellow | Red | Yellow | A, E, M, N |
| Pin | RG178 | 809-115 | M39029/76-425 | Yellow | Red | Green | A, E, M, N |
| Socket | RG174, RG316, RG179 | 809-116 | M39029/78-432 | Yellow | Orange | Red | A, E, M, N |
| Socket | RG178 | 809-117 | M39029/78-433 | Yellow | Orange | Orange | A, E, M, N |

#16 Socket Contact






Size #12 coaxial contacts


These #12 contacts accept 50 ohm and 75 ohm coaxial cable. Inner contact is rated at 1 amp, the outer contact 12 amps. DWV voltage rating is 1000 Vac rms sea level, 250 Vac at 50,000 feet. Contacts are packaged individually and shipped unassembled with instruction sheet. One contact consists of outer contact , fluorocarbon dielectric, inner contact and shield crimp sleeve. Inner and outer contacts are gold-plated copper alloy. Approved to SAE AS39029. VSWR rating 1.5:1 maximum up to 700 MHz. 5000 megohm insulation resistance.



#12 Socket Contact

| Type | Cable Size | Part Number | Military Part Number | Color Band | | | Tool |
|--------|---------------------|----------------|-------------------------|------------|-------|-------|------------|
| | | | | 1st | 2nd | 3rd | Code |
| Pin | RG174, RG316, RG179 | 809-118 | M39029/28-211 | Red | Brown | Brown | A, G, O, P |
| Pin | RG180 | 809-119 | M39029/28-409 | Yellow | Black | White | A, G, O, P |
| Socket | RG174, RG316, RG179 | 809-120 | M39029/27-210 | Red | Brown | Black | A, G, O, P |
| Socket | RG180 | 809-121 | M39029/27-402 | Yellow | Black | Red | A, G, O, P |





Dimensions in Inches (millimeters) are subject to change without notice.

© 2014 Glenair, Inc. Series 80 Mighty Mouse U.S. CAGE Code 06324 Printed in U.S.A.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Contacts category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

006-1189-20 71-VEAM 809-023 809-111 811393-000 850-014 97-45-1418P-5(920) 97-45-1418S-4 D-602-0106CS076 AIC12-14P

AIC16-16PG AIC8-12P AIC8-8SG AIC8-8SRAD 1495044-1 BACC47CP2T BACC47CP3S BACC47DP4 BACC47GC1A BACC47GN1

16968/2C 173-900245-91 21-033909-028 241611N001 2560-220-2031 27915-38T9 27964-38T112 2M809-118 97-67-36-20 AIC12-16P

AIC16-14SG AIC16-18PG AIC16-18S AIC16-20PG AIC4-4PG CE102S-18 M39029/30-221 M39029/77-430 416-2020-088I MDM
21SH003B-F222 48-100-5014P-02 BA-4020-50LD BA-4120-50LD BACC47CN2 BACC47GC3A BACC47GD3A BACC47GM1 52G137

REV A CB2-18-21PS D-602-1116CS2727