
## Size #16 coaxial contacts




These #16 contacts accept 50 ohm and 75 ohm coaxial cable. Inner contact is rated at 1 amp, the outer contact 12 amps. DWV voltage rating is 800 Vac rms sea level, 250 Vac at 50,000 feet. Contacts are packaged individually and are unassembled with instruction sheet. One contact consists of outer contact, fluorocarbon dielectric, inner contact and shield crimp sleeve. Inner and outer contacts are gold-plated copper alloy. Approved to SAE AS39029. VSWR rating 1.5:1 maximum up to 700 MHz. 5000 megohm insulation resistance.

Туре	Cable Size	Part Number	Military Part Number	Color Band			Tool Code
				1st	2nd	3rd	1001 Code
Pin	RG174, RG316, RG179	809-114	M39029/76-424	Yellow	Red	Yellow	A, E, M, N
Pin	RG178	809-115	M39029/76-425	Yellow	Red	Green	A, E, M, N
Socket	RG174, RG316, RG179	809-116	M39029/78-432	Yellow	Orange	Red	A, E, M, N
Socket	RG178	809-117	M39029/78-433	Yellow	Orange	Orange	A, E, M, N

#16 Socket Contact






## Size #12 coaxial contacts




These #12 contacts accept 50 ohm and 75 ohm coaxial cable. Inner contact is rated at 1 amp, the outer contact 12 amps. DWV voltage rating is 1000 Vac rms sea level, 250 Vac at 50,000 feet. Contacts are packaged individually and shipped unassembled with instruction sheet. One contact consists of outer contact, fluorocarbon dielectric, inner contact and shield crimp sleeve. Inner and outer contacts are gold-plated copper alloy. Approved to SAE AS39029. VSWR rating 1.5:1 maximum up to 700 MHz. 5000 megohm insulation resistance.

**Color Band Part Military Part** Tool **Cable Size** Type Number Number Code 1st 2nd 3rd Pin RG174, RG316, RG179 809-118 M39029/28-211 A, G, O, P Red Brown Brown M39029/28-409 A, G, O, P Pin RG180 809-119 Yellow Black White Socket RG174, RG316, RG179 809-120 M39029/27-210 A, G, O, P Red Brown Black Socket RG180 809-121 M39029/27-402 Yellow Black A, G, O, P Red

#12 Socket Contact





Dimensions in Inches (millimeters) are subject to change without notice.

© 2014 Glenair, Inc. Series 80 Mighty Mouse U.S. CAGE Code 06324

Printed in U.S.A.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Contacts category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

006-1189-20 71-VEAM 809-023 809-111 811393-000 850-014 97-45-1418P-5(920) 97-45-1418S-4 D-602-0106CS076 AIC12-14P

AIC16-16PG AIC8-12P AIC8-8SG AIC8-8SRAD 1495044-1 BACC47CP2T BACC47CP3S BACC47DP4 BACC47GC1A BACC47GN1

16968/2C 173-900245-91 21-033909-028 241611N001 2560-220-2031 27915-38T9 27964-38T112 2M809-118 97-67-36-20 AIC12-16P

AIC16-14SG AIC16-18PG AIC16-18S AIC16-20PG AIC4-4PG CE102S-18 M39029/30-221 M39029/77-430 416-2020-088I MDM
21SH003B-F222 48-100-5014P-02 BA-4020-50LD BA-4120-50LD BACC47CN2 BACC47GC3A BACC47GD3A BACC47GM1 52G137

REV A CB2-18-21PS D-602-1116CS2727