## M39029/90 853-001 Size 8 Concentric Twinax Pin



Size #8 Concentric Twinax Pin for MIL-DTL-38999 Series I, II, III and IV Connectors (Inactive for New Design—Replaced by M39029/113)



These #8 concentric twinax pin contacts accept MIL-STD-1553 data bus twinax cable. Center and intermediate contacts are rated at 1 amp, the outer contact 12 amps. DWV rating is 500 Vac rms sea level, 125 Vac at 70,000 feet. Operating frequency is 0-20 MHz. Contacts are packaged individually and shipped unassembled with instruction sheet. One contact consists of outer contact, fluorocarbon dielectric, inner contact, intermediate contact and shield crimp bushing. All contacts are gold-plated copper alloy. Approved to SAE AS39029. 5000 megohm insulation resistance. Mates with: M39029/91.

	Cable		Military Part Number	Color Band		
Туре	Accommodation	Part Number		1st	2nd	3rd
Pin	M17/176-00002	853-001-08-529	M39029/90-529	Green	Red	White

Б

© 2011 Glenair, Inc. CAGE Code 06324 Printed in U.S.A.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Contacts category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

006-1189-20 71-VEAM 809-023 809-111 811393-000 850-014 97-45-1418P-5(920) 97-45-1418S-4 D-602-0106CS076 AIC12-14P

AIC16-16PG AIC8-12P AIC8-8SG AIC8-8SRAD 1495044-1 BACC47CP2T BACC47CP3S BACC47DP4 BACC47GC1A BACC47GN1

16968/2C 173-900245-91 21-033909-028 241611N001 2560-220-2031 27915-38T9 27964-38T112 2M809-118 97-67-36-20 AIC12-16P

AIC16-14SG AIC16-18PG AIC16-18S AIC16-20PG AIC4-4PG CE102S-18 M39029/30-221 M39029/77-430 416-2020-088I MDM
21SH003B-F222 48-100-5014P-02 BA-4020-50LD BA-4120-50LD BACC47CN2 BACC47GC3A BACC47GD3A BACC47GM1 52G137

REV A CB2-18-21PS D-602-1116CS2727