

AS85049/49-2 and MS27506 Straight Strain Relief Self-Locking or Non-Self-Locking

CONNECTOR DESIGNATOR:

F MIL-DTL-27599, MIL-DTL-38999 Series I & II


FOR NEW DESIGN USE AS85049/121


Basic Part Number Dash No. M85049/49-2 S 10 W

S = Self-Locking Use Dash for Non-Self-Locking N = Non-Detented

Material and Finish Designator

- A = Aluminum, Black Anodize
- N = Aluminum, Electroless Nickel
- S = 300 Series Steel, Passivated
- **W** = Aluminum, 1000 Hour Cadmium Olive Drab over Electroless Nickel





Note: Screw orientation shown is for non-self-locking configuration. Screws on self-locking configurations are on the same side/face of the clamp.

TABLE I: Shell Size, Cable Entry and Backshell Dimensions												
Shell	Shell Size	A Thread	Ø E Max		F Max		Н		Cable Entry			
Size	Ref.	Class 2B	Self-Locking Only		Self-Locking Only		Max		Min		Max	
8	8/9	.438 - 28 UNEF	.86	(21.8)	.91	(23.1)	.85	(21.6)	.098	(2.5)	.234	(5.9)
10	10/11	.562 - 24 UNEF	.98	(24.9)	.91	(23.1)	.90	(22.9)	.153	(3.9)	.234	(5.9)
12	12/13	.688 - 24 UNEF	1.16	(29.5)	1.01	(25.7)	1.10	(27.9)	.190	(4.8)	.328	(8.3)
14	14/15	.813 - 20 UNEF	1.28	(32.5)	1.06	(26.9)	1.15	(29.2)	.260	(6.6)	.457	(11.6)
16	16/17	.938 - 20 UNEF	1.41	(35.8)	1.16	(29.5)	1.30	(33.0)	.283	(7.2)	.614	(15.6)
18	18/19	1.063 - 18 UNEF	1.52	(38.6)	1.41	(35.8)	1.50	(38.1)	.325	(8.3)	.634	(16.1)
20	20/21	1.188 - 18 UNEF	1.64	(41.7)	1.51	(38.4)	1.60	(40.6)	.343	(8.7)	.698	(17.7)
22	22/23	1.313 - 18 UNEF	1.77	(45.0)	1.66	(42.2)	1.70	(43.2)	.381	(9.7)	.823	(20.9)
24	24/25	1.438 - 18 UNEF	1.89	(48.0)	1.76	(44.7)	1.80	(45.7)	.418	(10.6)	.853	(21.7)

APPLICATION NOTES

- 1. Assembly to be identified with manufacturer's name and part number, space permitting.
- 2. Cable Entry is defined as the accommodation entry for the wire bundle or cable. Dimensions are not intended for inspection criteria.
- 3. For complete dimensions, see the applicable Military Specification.
- 4. Metric dimensions (mm) are in parentheses.

Dimensions in inches (millimeters) and are subject to change without notice.

© 2013 Glenair, Inc. U.S. CAGE Code 06324 Printed in U.S.A.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Backshells category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

60-036152-022 610HS012M15 M28840/504WA M28840/805WB M28840/809WA M28840/815WA M28840/816WA 627AS017M14
627MA124M14S 655HS002NF11 CW3899-000 M85049/10-134S M85049/10-17S M85049/10-33S M85049/10-94W M85049/11-28N
M85049/11-37N M85049/11-53N M85049/11-63N M85049/124-23W M85049/1720N04B M85049/1821W05C M85049/1825W06C
M85049/1919N05 M85049/23-74W M85049/24-71N M85049/25-47N M85049/25-94W M85049/27S12N M85049/39-11S M85049/39-17S
M85049/39-9S M85049/6-10B M85049/6-19N M85049/6-20B M85049/77-20W04 M85049/78-11N03 M85049/78-15W02 M85049/7817N04 M85049/78-19N05 M85049/79-19N07 M85049/79-25N04 M85049/82-18N02 M85049/82-22P02 M85049/83-10W03 M85049/8420N03 M85049/8-48N M85049/85-24N01 M85049/85-24P01 M85049/86-16P03