

AS85049/63 90° Qwik-Ty Strain Relief Optional Self-Locking • Optional Ground Lug

CONNECTOR DESIGNATOR: | MIL-DTL-38999 Series | and ||

Configuration N = Non-Detented

- G = Self-Locking with Ground Lug
- H = Non-Detented with Ground LugS = Self-Locking without Ground Lug

Finish

- A = Anodize, Black
- N = Electroless Nickel
- W = 1,000 Hour Cadmium Olive Drab over Electroless Nickel
- X = Nickel Fluorocarbon Polymer
- Y = Pure Dense Electrodeposited Aluminum

OPTIONAL

SELF-LOCKING

COUPLING

Z = Zinc-Nickel, Black

= Non Self-Locking **Basic Part Number** M85049/63 16 $M85049/63 = 90^{\circ}$ Shell Size K Self Lock C/E * MS3367-1 Tie Strap or Equivalent (Typical) Ground Lug

(G Option)

TABLE I: Shell Size, Thread, Cable Entry and Backshell Dimensions												
Shell Size Series II	Series I Shell Size Ref.	A Thread Class 2B	C Dia Max		E Dia Max		F Cable Entry		J Max		K Self-Locking	
8	9	.438-28 UNEF	.750	(19.1)	.860	(21.8)	.264	(6.7)	1.220	(31.0)	.630	(16.0)
10	11	.562-24 UNEF	.850	(21.6)	.980	(24.9)	.392	(10.0)	1.290	(32.8)	.630	(16.0)
12	13	.688-24 UNEF	1.000	(25.4)	1.160	(29.5)	.506	(12.9)	1.620	(41.1)	.630	(16.0)
14	15	.813-20 UNEF	1.100	(27.9)	1.280	(32.5)	.631	(16.0)	1.660	(42.2)	.700	(17.8)
16	17	.938-20 UNEF	1.250	(31.8)	1.410	(35.8)	.756	(19.2)	1.720	(43.7)	.700	(17.8)
18	19	1.063-18 UNEF	1.400	(35.6)	1.520	(38.6)	.845	(21.5)	1.720	(43.7)	.730	(18.5)
20	21	1.188-18 UNEF	1.500	(38.1)	1.640	(41.7)	.970	(24.6)	1.790	(45.5)	.730	(18.5)
22	23	1.313-18 UNEF	1.650	(41.9)	1.770	(45.0)	1.095	(27.8)	1.850	(47.0)	.730	(18.5)
24	25	1.438-18 UNEF	1.750	(44.5)	1.890	(48.0)	1.220	(31.0)	1.910	(48.5)	.730	(18.5)

APPLICATION NOTES

- 1. Assembly identified with manufacturer's name and part number, space permitting.
- 2. For complete dimensions, see the applicable Military Specification.
- 3. Cable entry is defined as the accomodation range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
- 4. Metric dimensions (mm) are in parentheses.

Dimensions in inches (millimeters) and are subject to change without notice.

© 2013 Glenair, Inc. U.S. CAGE Code 06324 Printed in U.S.A.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Strain Reliefs & Adapters category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

896227-000 899170S004 0113-023-000 6000-063-0022 CS6624-000 620AB038Z136 620AS001Z108 620AS038Z112 620AS038Z120 620AS038Z132 620FB038NF08 620HA038NF09 620HA038NF11 620HA038NF13 620HA038NF25 620HB049NF17 620HS038NF11 620HS038Z121 620HS042XM19 620HS042XM25 620HS048B17 620MS064NF12 620MS065Z107 620MS065ZNU06 627-123NF21-11 627-125NF23-6 630J041M06H 630J041M20H 637S010NF0212H 637S010NF0416A 640830-000 659943-000 66241-10A CW0597-000 CW0598-000 CW0948-000 CY0122-000 M85049/41-6A W/B M85049/42-12DS M85049/47N8 M85049/51-1-14S M85049/51S16S M85049/60-1N16 M85049/60-2G12W M85049/69-11N CZ3661-000 D02922-000 70.360.1628.0 703797-000 705825-000