

### Light, Solar, UVA Meters



#### Description:

The H110 Series meters from Anaheim Scientific include options for measuring Illumination (H117), Solar (H115, H117), and UVA lighting (H116, H117). Lightweight, handheld and durable, the H110 Series meters will provide years of reliable service. The H110 Series features:

#### Features:

- Convenient easy to read 3¾ digit display
- Real time data
- Data hold function
- Auto ranging
- Back light
- Auto power off and disable auto power off
- USB PC interface
- Data logging capacity up to 45,000 readings
- Low battery indicator
- Over load indicator
- Maximum/Minimum/Average record and elapse time
- Auto zero adjustment

#### Applications:

- Warehouse & Factory Lighting
- Photography and Videography
- UV Curing
- Solar Power Evaluation
- Energy Audits
- Museums & Art Galleries
- Stadium lighting
- Sun tanning beds

The H110 Series of light meters offers 3 models with different light sensors

Model #	Sensor
H115	Solar Power
H116	UVA
H117	Solar Power, UVA, and Light



H116  
UVA Meter



WARRANTY



### General Specifications

<b>Battery Life</b>	Approximately. 100 hours
<b>Display</b>	3 ¾ LCD
<b>Sampling</b>	4 times/second
<b>Power Off</b>	Manual by push button or auto shut off after approx. 30 minutes
<b>Data Output</b>	USB PC serial interface
<b>Datalogging Capacity</b>	Up to 45,000 reading
<b>Power</b>	9v battery or AC to DC Adaptor (9v/300mA)
<b>Dimensions</b>	130(L) x 56(W) x 38(H) mm
<b>Weight</b>	250g
<b>Current Consumption</b>	≤10 mA
<b>Sensor Length</b>	1 meter

### Light Sensor (H117)

<b>Sensor</b>	Silicon photodiode and filter
<b>Measuring Range</b>	40.00, 400.0, 4000, 40000, 400000 Lux 40, 400, 4000, 40000 Foot-candles
<b>Resolution</b>	0.01, 0.1, 1, 10, 100 Lux
<b>Accuracy</b>	±3% (Calibrated to standard incandescent lamp 2856° K) 6% other visible light source
<b>Angle Deviation from Cosine Characteristics</b>	30° ±2% 60° ±6% 80° ±25%
<b>Spectral Response</b>	400 – 1100 nm
<b>Peak Sensitivity Wavelength</b>	550 nm
<b>Auto Measurement &amp; Ranges</b>	0.01 W/m <sup>2</sup> ~ 2000 W/m <sup>2</sup> [0.01 Btu/(h*ft <sup>2</sup> ) ~ 634 Btu/(h*ft <sup>2</sup> )]

### UVA Sensor (H116, H117)

<b>Range</b>	40.0 μW/cm <sup>2</sup> , 400 μW/cm <sup>2</sup> , 20 mW/cm <sup>2</sup>
<b>Resolution</b>	0.1 μW/cm <sup>2</sup> , 1 μW/cm <sup>2</sup> , 0.01 mW/cm <sup>2</sup>
<b>Accuracy</b>	± (4%.F.S + 2dgt)
<b>Spectral Response</b>	320 – 400 nm
<b>Peak Sensitivity Wavelength</b>	365 nm
<b>Sensor</b>	Photo diode & UVA color correction filter

#### Includes:

- Meter
- Sensor
- Carrying Case
- DC Adaptor
- 9V Battery
- Mini USB to USB A Cable
- User Manual
- Installation CD

#### This instrument conforms to:

- EN61326-1 (2006)
- JISC 1609:1993
- CNS 5519

### Solar Power Sensor (H115, H117)

<b>Measuring Range</b>	40.00 W/m <sup>2</sup> , 400.0 W/m <sup>2</sup> , 2000 W/m <sup>2</sup> [13 Btu/(h*ft <sup>2</sup> ), 127 Btu/(h*ft <sup>2</sup> ), 634 Btu/(h*ft <sup>2</sup> )]
<b>Resolution</b>	0.01 W/m <sup>2</sup> , 0.1 W/m <sup>2</sup> , 1 W/m <sup>2</sup> [0.01 Btu/(h*ft <sup>2</sup> ), 0.1 Btu/(h*ft <sup>2</sup> ), 1 Btu/(h*ft <sup>2</sup> )]
<b>Accuracy</b>	Typically within ± 10 W/m <sup>2</sup> [ ±3 Btu/(h*ft <sup>2</sup> ) ] or ±5%, whichever is greater in sunlight. Additional temperature induced error ±0.38 W/m <sup>2</sup> / °C [ ±0.12 Btu/(h*ft <sup>2</sup> ) / °C] from 25°C
<b>Spectral Response</b>	400 – 1100 nm
<b>Auto Measurement &amp; Ranges</b>	0.01 W/m <sup>2</sup> ~ 2000 W/m <sup>2</sup> [0.01 Btu/(h*ft <sup>2</sup> ) ~ 634 Btu/(h*ft <sup>2</sup> )]

### H115

- Solar Power Meter

### H116

- UVA Meter

### H117

- Illumination Meter
- Solar Power Meter
- UVA Meter



H117  
Light, UVA, Solar  
Meter

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Environmental Test Equipment](#) *category:*

*Click to view products by* [Global Specialties](#) *manufacturer:*

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [2837806](#) [4328074](#) [4366444](#) [S-11](#) [382153](#) [700PTP-1](#) [GEO-](#)  
[CABLE-REEL-50M](#) [H115](#) [H300](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-H2S-100](#) [AW-NmHc-100](#) [ES1-CO-1000-01](#) [P 2801](#) [P 2802](#) [TM-197](#)  
[ULD-420-EUR](#) [TM-192](#) [TM-192D](#) [TM-305U](#) [UT309C](#) [EL-P-TC-T-SURFACE](#) [1500000059](#) [HS115](#) [MR59](#) [12227021](#) [13123602](#) [13123661](#)  
[12255930](#) [12983030](#) [30171091](#) [30198712](#) [30198755](#) [30209323](#) [12228657](#) [12229067](#) [12230090](#) [7358958](#) [12231398](#) [12231487](#) [7390674](#)  
[7390682](#) [12231550](#)