### ANAHEIM SCIENTIFIC

Measuring the World Around You

## M110 Data Sheet

# Mini Light Meter



#### **Description:**

With this meter you can measure illuminance from fluorescent, metal halide, high-pressure sodium and incandescent sources. Giving units in both Lux and Foot-candles, the M110 is durable, reliable, and easy to use. The M110 features:

#### Features:

- Overload indicator: LCD screen will show "OL" on the upper left-hand corner
- Low battery indicator "••••"
- Sampling rate: 2.5 times per second for digital display
- Spectral response close to CIE luminous spectral efficiency
- Cosine angular corrected
- According to JIS C 1609:1993 and CNS 5119 general A class Specifications
- Lux or foot-candle units
- Many applications include: Warehouses, factories, office buildings, restaurants, schools, library, hospitals, photographic, many video, parking garages, museums, art galleries, stadiums, building security
- Data hold (HOLD)
- Maximum/Average/Minimum Hold (MAX/MIN)
- Zero adjustment (ZERO)
- Auto power off and disable function
- Auto ranging

#### **Applications:**

- Warehouse & Factory Lighting
- Photography and Videography
- Energy Audits
- Museums & Art Galleries 3¾
- Stadium lighting







## ANAHEIM SCIENTIFIC

Technical Specifications		
Display	4000 count, maximum display 3999	
Sensor	Silicon photodiode and filter	
Measuring Range	400,4000, 40000,400000 Lux 40,400,4000,40000 Foot-candles	
Angle deviation from cosine characteristics	30°	±2%
	60 °	±6%
	80 °	±25%
Power Supply	2 batteries 1.5V AAA	
Accuracy	±3% ±3Lux(0~500Lux), ±3%(above 501 Lux) (Calibrated to standard incandescent lamp 2856°K) 8% other visible light source	
Battery life	About 200 hours	
Operating Conditions	5°C ~ 40°C, 0%~ 80%RH, ≤2km altitude	
Storage Conditions	-10°C ~ 60°C,	0%~ 70%RH
Dimensions	133(L) x 48(W) x 23(D) mm 5.3(L) x 1.9(W) x 0.2(D) inch	
Weight	80g (including battery)	
Accessories	User's manual, carrying case, 2x 1.5V battery	
Warranty	Limited two-year warranty	



#### Includes:

- Meter
- User Manual
- Carrying Case
- 2x 1.5V AAA Batteries

#### This instrument conforms to:

- EN61326-1 (2006)
- IEC 61000-4-2(2008, IEC 61000-4-3(2006) + (2007) CE

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Global Specialties manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS 2837806 4328074 4366444 S-11 382153 700PTP-1 GEO-CABLE-REEL-50M H115 H300 F150-SLC50 AW-CO-1000 AW-H2S-100 AW-NmHc-100 ES1-CO-1000-01 P 2801 P 2802 TM-197 ULD-420-EUR TM-192 TM-192D TM-305U UT309C EL-P-TC-T-SURFACE 1500000059 HS115 MR59 12227021 13123602 13123661 12255930 12983030 30171091 30198712 30198755 30209323 12228657 12229067 12230090 7358958 12231398 12231487 7390674 7390682 12231550