


Proto-Boards[®], Solderless Breadboards & Accessories

QT-59S

Quick Test Sockets

- Solderless socket and bus strips
- Molded-in mounting holes
- Vinyl back prevents shorting
- Replaceable nickel-silver spring clip contacts
- Accepts all components with leads up to .033 inches
- Conductive spring clips inside breadboard body grab component leads and connecting wires, AWG #22-30, securely
- Parts plug-in/pull-out without soldering or damage
- Patented tab/keyway features for simple interlocking of several breadboards into larger, more versatile arrays
- Standard 0.1-by-0.1 inch contact grid accommodates DIP ICs and virtually all modern active and passive components
- Molded tab/keyway feature interlocks



adjoining elements
into larger array.

- Sockets provide twin columns of 5-point spring contact clips on each side of a 0.3-inch center channel.
- Bus Strips provide twin rows of pre-connected 5-point contact clips.
- MOUNTING
Molded-in mounting holes; mount with 4-40 flat head screws from top or 6-32F self-tapping screws from behind
- WIRE SIZE
#22 AWG wire preferred; component leads with diameters .01-.033 inches (.25-.84mm) acceptable, .015-.032 inches (.38-.81mm) recommended; prepared wire kit WK-1 is available
- HEIGHT
All Quick Test breadboards are 0.33 inches (8mm) high
- RESISTANCE
Initial contact resistance is less than 0.5 milliohm, after multiple uses, this reduces to less than 0.4 milliohm

QT-59S

Mount Dimen	6.2 in (157mm)
Strip Length	6.5 in (165mm)
Strip Width	1.32 in (34mm)
Tie Points	590
Term Clips	118
IC Qty	8
Part Number	101-1059

Proto-Boards® *Global's premium brand*

SOLDERLESS PROTO-BOARDS®


NEW!



PB-10 **PB-60** **PB-70** **PB-83** **PB-103** **PB-104** **PB-105**

IC Capacity	8	16	12	8	24	32	48
Terminals					450	612	912
Tie Points	840	1680	1260	840	2250	3060	4560
Binding Posts	3	4	3	3	4	4	5
Length	7.0 in	6 in.	8.5 in	7 in.	9 in.	9.8 in.	9.2 in.
Width	4.0 in	6.5 in.	5 in	4.0 in.	6 in.	8 in.	11.4 in.
Height	1.4 in	1.4 in.	1.4 in	1.4 in.	1.4 in	1.4 in	1.4 in
P/N	104-1000	104-6000	104-1070	104-0083	104-1030	104-1040	104-1050
Assembly Required	N/A	N/A	Yes	Yes	N/A	N/A	N/A

Back



Clear Plexiglass plate leaves the pin layout and bus strip pin connections clearly visible!


JUMPER WIRE KIT



WK-1

- Contains pre-cut/pre-stripped/pre-formed AWG#22 insulated solid hookup wire
- 25 pieces each of 14 color-coded lengths - 0.1 through 5.0 inches for a total of 350 wires
- Compartmental plastic case
- Each group of wires are individually wrapped to prevent mix-up

MATCHBOARD



EXP-300PC

- Prepared printed circuit board pre-etched and drilled
- Duplicate hole-and-connection pattern of EXP-300
- Use to provide a permanent hard-wired version of your circuit (components not included)

The Only Breadboard You'll Ever Need:

- Nickel silver alloy pins are pre-stressed, spring loaded and non-corrosive for long term reliability
- Molded in rugged thermoplastic for durability and high temperature application
- Heavy mylar backing eliminates possibility of short circuits
- Limited lifetime warranty

	MODEL	CENTER	STRIP LENGTH	STRIP WIDTH	TIE POINTS	TERM CLIPS	IC QTY
	UBS-100	0.3 in	6.5 in	2.2 in	840	168	8 (14-pin)
	EXP-300	0.3 in	6.0 in	2.1 in	550	110	6 (14-pin)
	EXP-350	0.3 in	3.6 in	2.1 in	270	54	3 (14-pin)
	MODEL	Mount Dimen.	STRIP LENGTH	STRIP WIDTH	TIE POINTS	TERM CLIPS	IC QTY
	QT-59S	6.2 in	6.5 in	1.32 in	590	118	8
	QT-59B	6.2 in	6.5 in	0.36 in	100	20	n/a
	QT-47S	1.0 in	5.3 in	1.32 in	470	94	6
	QT-47B	5.0	5.3 in	0.36 in	80	16	n/a
	QT-35S	3.8 in	4.1 in	1.32 in	350	70	5
	QT-35B	3.8 in	4.1 in	0.36 in	60	12	n/a

Full specifications available on our website: www.globalspecialties.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for PCBs & Breadboards category:

Click to view products by Global Specialties manufacturer:

Other Similar products are found below :

[8016](#) [1320833-1](#) [3410](#) [3396](#) [8006](#) [8015](#) [8019](#) [8026](#) [1239-19](#) [32P15WE](#) [ZAS1X206203XRPU160](#) [7115](#) [RE013-LF](#) [RE014-LF](#) [RE1210-LF](#)
[RE200-C3](#) [RE317-HP](#) [RE320-LFDS](#) [RE438-LF](#) [RE510-S2](#) [RE510-S3](#) [RE904](#) [RE917](#) [RE932-02](#) [RE932-06](#) [RE933-02](#) [RE933-04](#) [RE935-](#)
[02E](#) [RE935-02R](#) [RE935-05R](#) [RE936-08](#) [RE943-S3](#) [RE944-S1](#) [RE944-S2](#) [RE944-S3](#) [RE945-S1](#) [MB-1](#) [MB-10](#) [4225](#) [4796](#) [TW-E40-1020-P](#)
[15073](#) [15071](#) [15069](#) [15068](#) [15075](#) [15079](#) [15078](#) [141301](#) [141302](#)