

WK-2

JUMPER WIRE KIT 140 PCS




Applications

Use the WK-2 Jumper Wire Kit for prototyping wire connections. It is specifically designed for use on Global Specialties trainers such as the:

- PB-507
- PB-505
- PB-503
- PB-502
- PB-501
- PB-500
- And all Global Specialties Solderless Breadboards

Overview

The WK-2 Wire Kit contains 140 pre-cut, pre-stripped and pre-formed #22 gauge insulated solid hookup wires. The WK-2 consists of 10 each of 14 different sized, color-coded lengths of 125 mm through 3 mm. The WK-2 comes in a compartmentalized plastic case and each group of wires is individually wrapped to prevent mix-ups in shipping.



Features

- Solid hook-up wires
- PVC insulation
- RoHS compliant
- 10 pieces each of:
 - ▶ 125 mm green
 - ▶ 100 mm yellow
 - ▶ 78 mm orange
 - ▶ 50 mm red
 - ▶ 25 mm brown
 - ▶ 23 mm white
 - ▶ 20 mm grey
 - ▶ 18 mm violet
 - ▶ 15 mm blue
 - ▶ 12 mm green
 - ▶ 10 mm yellow
 - ▶ 7 mm orange
 - ▶ 5 mm red
 - ▶ 3 mm bare

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Jumper Wires](#) category:

Click to view products by [Global Specialties](#) manufacturer:

Other Similar products are found below :

[420688201-3](#) [PCIEC-064-1000-EC-EM-P-85](#) [PCIEC-064-0500-EC-EM-P-85](#) [MIKROE-1388](#) [MIKROE-2022](#) [BC-32626](#) [BC-32678](#) [920-0137-01](#) [920-0164-01](#) [920-0163-01](#) [920-0162-01](#) [920-0189-01](#) [920-0195-50](#) [920-0192-50](#) [920-0191-01](#) [920-0190-01](#) [920-0188-01](#) [920-0187-01](#) [920-0183-01](#) [920-0176-01](#) [920-0156-50](#) [920-0155-50](#) [920-0085-01](#) [TW-AM-6](#) [ICTC-MP](#) [ICTC-FP](#) [240-006](#) [923345-01-C](#) [923345-02-C](#) [923345-03-C](#) [923345-04-C](#) [923345-05-C](#) [923345-06-C](#) [923345-07-C](#) [923345-09-C](#) [923345-20-C](#) [923345-30-C](#) [923345-40-C](#) [923345-50-C](#) [923351-I](#) [BC-32670](#) [BC-32671](#) [BC-32672](#) [920-0143-01](#) [920-0145-01](#) [920-0177-01](#) [920-0178-01](#) [920-0179-01](#) [920-0181-01](#) [920-0184-01](#)