

GN 480

Flanged bolts









Application example





technical informations

Material

Steel, zinc-plated, blue passivated.

Features and applications

Flanged bolts GN 480 are used in connection with clamp mountings, as foot or as connecting element, e.g. for adjustments in width and height.

With their low flange height, they provide an alternative for the foot clamp mounting GN 473 in applications where clamping is required at low height above the clamping surface.

The bore spacing m of the foot clamp mounting GN 480 is matched with the clamp mountings GN 473 and GN 477 as well as retaining magnets GN 51.6.

Standard Elements	Main dimensions							Weight	
Description	d ₁	I ₁	b	d ₂	d ₃	12	13	m	g
GN 480-8-18	8	18	14	31.5	M 4	6	2	22	23
GN 480-8-32	8	32	14	31.5	M 4	6	2	22	40
GN 480-10-21	10	21	16	38	M 5	8	2.5	27	43
GN 480-10-37	10	37	16	38	M 5	8	2.5	27	52
GN 480-12-22	12	22	16	38	M 5	8	2.5	27	49

GN 480-12-39	12	39	16	38	M 5	8	2.5	27	64
GN 480-15-27.5	15	27.5	20	45	M 6	10	4	32	94
GN 480-15-47.5	15	47.5	20	45	M 6	10	4	32	122
GN 480-16-28	16	28	20	45	M 6	10	4	32	100
GN 480-16-49	16	49	20	45	M 6	10	4	32	133
GN 480-20-35	20	35	25	50	M 6	10	-	36	166
GN 480-20-60	20	60	25	50	M 6	10	4	36	228



STANDARD MACHINE ELEMENTS WORLDWIDE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Elesa & Ganter manufacturer:

Other Similar products are found below:

EC18-WELL FMD411 SA9Z-F11 E4R-R12A-CS3M010 E4R-R12A-CS3M020 BS-1T CHITAN ICAB-1 SA9Z-S07PN02 ECT18-WELL 57142-000 79450811 734209100 ASI M12 VS 440148 430233 440101 440102 440121 440122 440131 440132 440135 440147 XSZB108 Y92E-BC12 Y92E-BC18 10901 0909 UAC 101 810-12AC/DC 843-12AC/DC 844-12AC/DC 771000-6011 771000-6202 812-12AC/DC 834-12AC/DC 909G 910G 913G 92.031.9058.1 92.032.9058.1 925G 771000-6010 GN 473-B12-MT GN 474-B12-B12-MT GN 474-B16-B16-MT GN 479-B12-30 XSZB118 XSZB112 XSZB130 611-12DC 08 2424 010 000 733877001 ELST-M PG9