



Pin-Belegung / Pin Assignment

	P1	P2
CC	A5	A5
DP	A6	A6
DN	A7	A7
SBU1	A8	A8
Vconn	B5	B5
SBU2	B8	B8
SSTXp1	A2	A2
SSTXn1	A3	A3
SSRXp2	A11	A11
SSRXn2	A10	A10
SSTXp2	B2	B2
SSTXn2	B3	B3
SSRXp1	B11	B11
SSRXn1	B10	B10
GND (A1,A12,B1,B12)	Shell	Shell
VBUS (A4,A9,B4,B9)	A4,A9,B4,B9	A4,A9,B4,B9

P1



6.65 ± 0.2

120 ± 10

22.0 ± 0.2

40

47

P2

11.5

11.2 ± 0.1

20.45 ± 0.1

USB-C™-Adapter auf DisplayPort und HDMI™

- Multi-Monitor-Adapter zum Spiegeln von Daten, Audio- und Videosignalen über USB-C™ auf bis zu 1 HDMI™- und 1 DisplayPort-Gerät
- unterstützt HDR (High Dynamic Range) für kontrastreiche Bilder sowie HDCP 1.4, 2.2 und 2.3 für geschützte Signalübertragung

Anschlüsse:	USB-C™-Stecker, 1x DisplayPort-1.4-Buchse, 1x HDMI™-2.1-Buchse (Typ A)
Max. Datenübertragungsrate:	18 Gbit/s
Max. Auflösung:	4K @ 60 Hz für beide Ausgänge, (Max. 4K @ 30 Hz für ASUS [VP28U])
Material Innenleiter:	Kupfer (Cu)
Material:	TPE 45P, PC, ABS
AD Kabelmantel:	5,0 mm
Gewicht:	25 g
Leistungsverbrauch im Bereitschaftszustand:	0,7 W
Betriebstemperatur:	0 °C ~ +45 °C
Betriebsfeuchtigkeit:	10 % ~ 85 % RH (ohne Kondensation)
Lagertemperatur:	-10 °C ~ +70 °C
Lagerfeuchtigkeit:	5 % ~ 90 % RH (ohne Kondensation)

USB-C™ to DisplayPort and HDMI™ Adapter

- multi-monitor adapter for mirroring data, audio and video signals via USB-C™ to up to 1 HDMI™ and 1 DisplayPort device
- supports HDR (High Dynamic Range) for high-contrast images and HDCP 1.4, 2.2 and 2.3 for protected signal transmission

Connectors:	USB-C™ plug, 1x DisplayPort 1.4 socket, 1x HDMI™ 2.1 socket (Type A)
Max. data transmission rate:	18 Gbit/s
Max. resolution:	Max. 4K @ 60 Hz for both outputs, (Max. 4K @ 30 Hz on ASUS [VP28U])
Material inner conductor:	Copper (Cu)
Material:	TPE 45P, PC, ABS
OD cable jacket:	5.0 mm
Weight:	25 g
Standby power consumption:	0.7 W
Operating temperature:	0 °C ~ +45 °C
Operating humidity:	10 % ~ 85 % RH (no condensation)
Storage temperature:	-10 °C ~ +70 °C
Storage humidity:	5 % ~ 90 % RH (no condensation)



Änderungen

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	23.02.2022	aw	1/1
		gepr.:	23.02.2022	aw	
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change				60172	



USB-C ADAP/DP1.2/HDMI
2x4k@60Hz SCHWARZ

Zeichnungs-Nr.:

60172

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Goobay](#) manufacturer:

Other Similar products are found below :

[1-3737-600-3216](#) [LF3BLX](#) [30-513](#) [28-511-0](#) [RCA05RCAB](#) [427493000-3](#) [49152A-010-S2](#) [32-3766](#) [32HR07284X](#) [CAB-LFH-V16A16S0](#)
[DB25M02XLRMXLRFY](#) [426052000-3](#) [LF1BKX](#) [TT746](#) [CA-MINIDP-DVIM-6FT](#) [CA-MINIDP-DVIM-3FT](#) [CA-MINIDP-DVIM-10FT](#)
[CA-MINIDP-VGAF-3FT](#) [CA-MINIDP-HDMIF-6FT](#) [MDC8P53](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [cab-DP to HDMI Passive](#) [VGA CABLE](#)
[DISPLAYPORT TO VGA CABLE](#) [TT3GNX](#) [1700021831-01](#) [Audio Cable](#) [427491690-3](#) [427528000-3](#) [TT2PX](#) [SPEAKER CABLE](#)
[L=300mm](#) [Speaker cable](#) [594E3412000E](#) [32007-005500-200-RS](#) [BCLBH](#) [BANHF](#) [BAPHG](#) [COQBI](#) [COQBG](#) [COEHG](#) [COJBI](#) [DAEBK](#)
[51771](#) [39448](#) [VAB-S04-L](#) [VAS-A13-B200](#) [VAS-A13-B300](#) [KABADA USBC/JACK OEM-C11](#)