



Art.-Nr. / Item No.	Beschreibung / Description	Länge / Length (L)	Kontaktwiderstand / Contact resistance	Kabelaufbau / Cable structure	AD Kabelmantel / OD cable jacket
61637	HDMI 2.1 Kabel 0050 0,5m STD sw LC	500 ± 15 mm	3 Ω max.	30AWG (1/0.254CCS*1P+E+A+M)*5+1/0.254CCS*4C+AEB) 144#/0.12mm/AL-MG	6.0 ± 0.2 mm
61638	HDMI 2.1 Kabel 0100 1,0m STD sw LC	1000 ± 20 mm	3 Ω max.	30AWG (1/0.254CCS*1P+E+A+M)*5+1/0.254CCS*4C+AEB) 144#/0.12mm/AL-MG	6.0 ± 0.2 mm
61639	HDMI 2.1 Kabel 0150 1,5m STD sw LC	1500 ± 30 mm	3 Ω max.	30AWG (1/0.254CCS*1P+E+A+M)*5+1/0.254CCS*4C+AEB) 144#/0.12mm/AL-MG	6.0 ± 0.2 mm
61640	HDMI 2.1 Kabel 0200 2,0m STD sw LC	2000 ± 30 mm	3 Ω max.	30AWG (1/0.254CCS*1P+E+A+M)*5+1/0.254CCS*4C+AEB) 144#/0.12mm/AL-MG	6.0 ± 0.2 mm
61641	HDMI 2.1 Kabel 0300 3,0m STD sw LC	3000 ± 50 mm	5 Ω max.	28AWG+30AWG (1/0.32CCS*1P+E+A+M)*5+1/0.254CCS*4C+AEB) 144#/0.12mm/AL-MG	7.0 ± 0.15 mm
61642	HDMI 2.1 Kabel 0500 5,0m STD sw LC	5000 ± 100 mm	5 Ω max.	26AWG+28AWG (1/0.40CCS*1P+E+A+M)*5+1/0.32CCS*4C+AEB) 160#/0.12mm/AL-MG	7.5 ± 0.2 mm

Ultra High-Speed HDMI™-Kabel mit Ethernet

- UHD-Signalübertragung mit bis zu 8K @ 60 Hz und 4K @ 120 Hz (abwärtskompatibel)
- vergoldete HDMI™-Steckverbinder
- integrierter Ethernet-Kanal
- reine Kupferleiter und 2-fache Schirmung

Anschlüsse: 2x HDMI™-Stecker (Typ A)

Material Kabelmantel: PVC

Max. Übertragungsrate: 48 Gbit/s

Isolationswiderstand: 300 V \Rightarrow , 10 MΩ min.

Unterstützte Videostandards: 4K Ultra HD 2160p (120 Hz), 8K Ultra HD 4320p (60 Hz)

Unterstützte Audiostandards: Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC)

Weitere unterstützte Standards: HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 3D, HDCP 2.2, Consumer Electronics Control (CEC)

Ultra High Speed HDMI™ Cable with Ethernet

- Ultra HD signal transmission with up to 8K @ 60 Hz and 4K @ 120 Hz (downward compatible)
- gold-plated HDMI™ connectors
- integrated Ethernet channel
- pure copper conductors and double shielding

Connections: 2x HDMI™ plug (Type A)

Material cable jacket: PVC

Max. data transmission rate: 48 Gbit/s

Insulation resistance: 300 V \Rightarrow , 10 MΩ min.

Supported video standards: 4K Ultra HD 2160p (120 Hz), 8K Ultra HD 4320p (60 Hz)

Supported audio standards: Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC)

Other supported standards: HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 3D, HDCP 2.2, Consumer Electronics Control (CEC)

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	28.10.2022	HDMI 2.1 Kabel XXXX Xm STD sw LC	1/1
		gepr.:	28.10.2022		
		Norm:			
Änderungen vorbehalten / Subject to change				Zeichnungs-Nr.:	von



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [HDMI, Displayport & DVI Connectors](#) category:

Click to view products by [Goobay](#) manufacturer:

Other Similar products are found below :

[30-528](#) [30-504](#) [33DVIR-24S1B](#) [47648-2000](#) [TC142X](#) [HAGBH](#) [AABII](#) [AAIBG](#) [AAIBH](#) [AANBG](#) [52355](#) [XHLJQ-00026](#) [HDMI-019R](#)
[G46M2013201AWEU](#) [ST-0277D00-052-142](#) [PJ-399M](#) [PJ-615-5A](#) [HDMI-S-125-D](#) [PJ-359](#) [PJ-3850-5A](#) [PJ-3250D-5A](#) [KH-PJ-359](#) [HDMI-](#)
[005-ARSW-L116](#) [58490](#) [DS-45404](#) [HD0039](#) [60616](#) [AAMBJ](#) [61275](#) [61297](#) [KABHD](#) [OEM-40](#) [61293](#) [DS-45316](#) [50355](#) [AK-330115-010-S](#)
[AK-330101-002-S](#) [AHCBI](#) [AK-330127-300-S](#) [CG526-B-3.0](#) [64866](#) [CG525-R-1.8](#) [61296](#) [CG865-3](#) [CG517-3.0](#) [EAEBD](#) [65262](#) [DB-340305-](#)
[018-S](#) [DS-55521](#) [ALGLI](#) [KABHD](#) [OEM-35](#)