



FEATURES



- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance


MECHANICAL DATA

- * Case: Molded plastic
- * Lead: Axial leads, solderable per MIL-STD-750, method 2026
- * Polarity:Polarity symbols marked on case
- * Marking: T4,T6

VOLTAGE RANGE 100Volts CURRENT

0.15 Ampere

SOD123




DIMENSIONS					
	INCHES		MILLIMETERS		
SYMBOL	MIN	MAX	MIN	MAX	
Α	0,037	0,053	0,95	1,35	
В	0,000	0,005	0,00	0,12	
С	-	0.008	-	0.20	
D	0.055	0.071	1.40	1.80	
E	0.098	0.110	2.50	2.80	
F	0.142	0.154	3.60	3.90	
G	0.016	3.	0.40	-	
Н	0.020	0.028	0,50	0.70	


MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Rating 25°C ambient temperature uniess otherwies specified. Single phase half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.


TYPE NUMBER	1N4148W	UNITS
Maximum Recurrent Peak Reverse Voltage	100	V
Maximum RMS Voltage	70	V
Maximum DC Blocking Voltage	100	V
Maximum Average Forward Rectified Current		
See Fig. 1	0.15	А
Peak Forward Surge Current @ t=1.0 µs	2.0	
@t =1.0s	1.0	А
Maximum Instantaneous Forward Voltage at 0.15A	1.25	V
Maximum DC Reverse Current Ta=25°C at Rated DC Blocking Voltage	1	μА
Typical Junction Capacitance	2	pF
Total Power Dissipation	400	mW
Maximum Reverse Recovery Time (TRR typical)	8	ns
Operating Temperature Range T _J	-55 to +150	°C
Storage Temperature Range Tstg	-55 to +150	°C

RATING AND CHARACTERISTIC CURVES 1N4148W









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by GOODWORK manufacturer:

Other Similar products are found below:

MMBD3004S-13-F RD0306T-H BAV17-TR BAV19-TR HSC285TRF-E 1N3611 NTE156A NTE574 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08 1N4454-TR BAV199E6433HTMA1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 NSVM1MA152WKT1G RGP30D-E3/73 BAV99TQ-13-F BAS21DWA-7 NTE6250 NTE582-4 NTE582-6 MMDB30-E28X