




# MBR2020CT THRU MBR20200CT

## 20.0 AMP SCHOTTKY BARRIER RECTIFIERS



### FEATURES

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability
- \* Good for switching mode application

### MECHANICAL DATA


- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Lead solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: As Marked
- \* Mounting position: Any

### VOLTAGE RANGE

20 to 200 Volts

### CURRENT

20.0 Amperes



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.  
Single phase half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

| TYPE NUMBER   | MBR2020CT  | MBR2045CT | MBR2060CT | MBR2080CT | MBR20100CT | MBR20150CT | MBR20200CT | UNITS |
|---|------------|-----------|-----------|-----------|------------|------------|------------|-------|
| Maximum Recurrent Peak Reverse Voltage  | 20         | 45        | 60        | 80        | 100        | 150        | 200        | V     |
| Maximum RMS Voltage   | 14         | 32        | 42        | 56        | 70         | 105        | 140        | V     |
| Maximum DC Blocking Voltage   | 20         | 45        | 60        | 80        | 100        | 150        | 200        | V     |
| Maximum Average Forward Rectified Current<br>at Tc=125°C  | 20         |           |           |           |            |            |            | A     |
| Peak Forward Surge Current, 8.3 ms single half sine-wave<br>superimposed on rated load (JEDEC method) | 200        |           |           |           |            |            |            | A     |
| Maximum Instantaneous Forward Voltage at 20A  | 0.55       | 0.7       | 0.85      |           | 0.92       |            | V          |       |
| Maximum DC Reverse Current<br>at Rated DC Blocking Voltage  | Ta=25°C    |           |           | 0.2       |            |            | mA         |       |
|   | Ta=100°C   |           |           | 50        |            |            | mA         |       |
| Typical Junction Capacitance (Note1)  | 500        |           |           |           |            |            |            | pF    |
| Typical Thermal Resistance RθJC (Note 2)  | 2.5        |           |           |           |            |            |            | °C/W  |
| Operating Temperature Range Tj  | -65 — +150 |           |           |           |            |            |            | °C    |
| Storage Temperature Range Tstg  | -65 — +150 |           |           |           |            |            |            | °C    |

#### NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Case.

## RATING AND CHARACTERISTIC CURVES (MBR2020CT THRU MBR20200CT)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5 - TYPICAL REVERSE CHARACTERISTICS





FIG.4-TYPICAL JUNCTION CAPACITANCE



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Schottky Diodes & Rectifiers](#) category:*

*Click to view products by [GOODWORK](#) manufacturer:*

Other Similar products are found below :

[MA4E2039](#) [MA4E2508M-1112](#) [MBR10100CT-BP](#) [MBR1545CT](#) [MMBD301M3T5G](#) [GS1JE-TP](#) [RB160M-50TR](#) [BAS 3010S-02LRH E6327](#)  
[BAT 54-02LRH E6327](#) [NSR05F40QNXT5G](#) [NSVR05F40NXT5G](#) [NTE555](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SBS818-TL-E](#) [SK310-T](#)  
[SK33A-TP](#) [SK34B-TP](#) [SS3003CH-TL-E](#) [PDS3100Q-7](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM](#) [MA4E2501L-1290](#) [MBRB30H30CT-1G](#)  
[DMJ3940-000](#) [SB007-03C-TB-E](#) [SK32A-TP](#) [SK33B-TP](#) [SK35A-TP](#) [SK38B-LTP](#) [SK38B-TP](#) [NRVBM120LT1G](#) [NTE505](#)  
[NTSB30U100CT-1G](#) [SS0503SH-TL-E](#) [VS-6CWQ10FNHM3](#) [CRG04\(T5L,TEMQ\)](#) [ACDBA1100LR-HF](#) [ACDBA1200-HF](#) [ACDBA2100-HF](#)  
[ACDBA240-HF](#) [ACDBA3100-HF](#) [CDBQC0530L-HF](#) [ACDBA260LR-HF](#) [ACDBA1100-HF](#) [MA4E2502L-1246](#) [10BQ060-M3/5BT](#)  
[NRVB130LSFT1G](#) [CRS08TE85LQM](#) [PMAD1108-LF](#)