


## SERIES 30 Sealed, Front Panel Mounting

#### **FEATURES**

- Threaded bushing
- · Choice of 6 button colors
- SPST (momentary contact)
- Gold plated contacts
- Strong, lightweight aluminum housing
- Sealed against dust and moisture to IP67 (to IP67 with silicone boot\*)



### **DIMENSIONS** in inches (and millimeters)



#### **RATING**

Cycles: 500,000 actuations

Operating Temperature: -40°C to +80°C

Shock: 100 G's/6 milliseconds

Travel: .090 nominal

Travel Before Make: .035 nominal Rating at 24 VDC: 150 milliamps Voltage Breakdown: 1000 Vac

Contact Resistance: 25 Megaohms max

(initial)

Insulation Resistance: 1,000 Megaohms

minimum

#### **MATERIAL**

**Housing:** Aluminum, black chrome finish **Button, Base, and Plunger:** Nylon, 45%

glass-filled

**Terminal:** Brass, gold-plated over nickel **Shorting Bar:** Brass, gold-plated over nickel

Internal Seal: Silicone rubber O-ring panel Seal: Silicone Spring: Tinned music wire

Hex Nut: 1/2-32, Brass with Nickel Plating,

P/N 635201

Lockwasher: Internal, 1/2 dia., Steel with


Zinc plating, P/N 635401

\* Switch meets IP67 without boot if not actuated during immersion

CIRCUITRY: SPST N.O.



#### **ORDERING INFORMATION**





# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Fixings category:

Click to view products by Grayhill manufacturer:

Other Similar products are found below:

893102000 00-5150 LZZ1A 0098.9234 61-9451.0 M2PA-5011 630155 635401 6PA113 6PA147-E6 6PA148-E6 6PA32 6PA9 700109
700303A56 700C1GRY 700C2GRN 704-6001 704.960.4 704.960.9 704.965.2 704.965.6 704.966.0 7089-3 710082-B11 71M1048
757200264 764300000 MHU35 MHU37 807039-1 825.003.011 825.005.011 825.053.011 825.055.011 826.000.071 827.020.011
827.400.021 835.900.023 MML52C10C MML52E10C MML92HGH MML93K 84211M02CNNS 84212M02CNNS 84217A8.0LNOS
842.500.011 843.000.011 843187-000 843487-000