

Green Cell

GC Snap

TYPE 2 EV CHARGING CABLE



Ergonomic shape
fit for users' needs



Flexible wire
convenient retraction



Resistant
water and damage
resistant



Hard case
included in the set

SPECIFICATION

Model	EVKABGC01	EVKABGC02	EVKABGC04
Voltage	1P 200–260 VAC 3P 380–440 VAC	1P 200–260 VAC 3P 380–440 VAC	1P 200–260 VAC 3P 380–440 VAC
Current	32 A	32 A	16 A
Total Power	22 kW	22 kW	11 kW
Input	Type 2	Type 2	Type 2
Output	Type 2	Type 2	Type 2
Cable length	5 m	7 m	7 m
Cable variant	5G6.0 + 2x0.5 mm ²	5G6.0 + 2x0.5 mm ²	5G2.5 + 2x0.5 mm ²
Cable ø: approx.	17.0 mm	17.0 mm	13.5 mm
Protection rating		IP54	
Ambient temperature rating		-35 °C to +50 °C	
Weight (+/- 50 g)	3.15 kg	4.45 kg	2.4 kg
Compliance with	EN IEC 61851-1:2019; EN 62196-2:2017; EN 62196-1:2014		



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables](#) category:

Click to view products by [Green Cell](#) manufacturer:

Other Similar products are found below :

[706000D02F200](#) [910640](#) [96CB-L2020PIB2](#) [AC172](#) [ACL-SSI-4](#) [1300150047](#) [1300660036](#) [1300660042](#) [1302260080](#) [1300150079](#)
[1300220119](#) [1301240492](#) [1365323-1](#) [1589946-2](#) [1971465-2](#) [20240400003](#) [20886510030](#) [2-22733-8](#) [3011-03](#) [SSM005PCODY012Q](#) [CCS-](#)
[FCB-5](#) [CCSFCBF2](#) [VMMP6R](#) [427492400-3](#) [05AD05X](#) [10075358-F0200YYLF](#) [1052015-1-10](#) [540012](#) [RTPADPTR02](#) [636083-1](#) [83010-](#)
[0157](#) [VMMP2BK](#) [VMMP1BK](#) [ENP2205M030](#) [5-1589943-0](#) [N12601](#) [1300660038](#) [1300150101](#) [1300140041](#) [1300660049](#) [1300300014](#)
[1300150058](#) [1300150050](#) [1300150031](#) [1300140064](#) [1200900023](#) [00-4951](#) [XW2Z100JF1](#) [1200900047](#) [C200H-CN220-EU](#)