



Applicable FPC

RECOMMEND PCB LAYOUT
TOLERANCE:±0.05

G-Switch Specification:

1. Current rated: 0.4A AC/DC
2. Voltage rating: 50V AC/DC
3. Withstanding voltage: 200V AC
4. Contact resistance: 20mΩ max.
5. Insulation resistance: 500MΩ min
6. Durability cycle: 30Cycles
7. Removal force: 0.21kgf/Pin min
8. Operating temperature range: -25°C ~ +85°C



GT-F0506 S R 20 -XX X XX 01

- G-Switch**
- Series No**
- Termipoint**
S-SMT
- Angle**
R-90°
- Terminal Plating**
MT- MATTE TIN
- Housing Colour**
S-Nature
- Pin Q' PY**
04~60
- Height**
20-2.0mm

Circuit	Dimensions(mm)			Circuit	Dimensions(mm)			Circuit	Dimensions(mm)		
	A	B	C		A	B	C		A	B	C
04	6.40	1.50	2.57	23	15.90	11.00	12.07	42	25.40	20.50	21.57
05	6.90	2.00	3.07	24	16.40	11.50	12.57	43	25.90	21.00	22.07
06	7.40	2.50	3.57	25	16.90	12.00	13.07	44	26.40	21.50	22.57
07	7.90	3.00	4.07	26	17.40	12.50	13.57	45	26.90	22.00	23.07
08	8.40	3.50	4.57	27	17.90	13.00	14.07	46	27.40	22.50	23.57
09	8.90	4.00	5.07	28	18.40	13.50	14.57	47	27.90	23.00	24.07
10	9.40	4.50	5.57	29	18.90	14.00	15.07	48	28.40	23.50	24.57
11	9.90	5.00	6.07	30	19.40	14.50	15.57	49	28.90	24.00	25.07
12	10.40	5.50	6.57	31	19.90	15.00	16.07	50	29.40	24.50	25.57
13	10.90	6.00	7.07	32	20.40	15.50	16.57	51	29.90	25.00	26.07
14	11.40	6.50	7.57	33	20.90	16.00	17.07	52	30.40	25.50	26.57
15	11.90	7.00	8.07	34	21.40	16.50	17.57	53	30.90	26.00	27.07
16	12.40	7.50	8.57	35	21.90	17.00	18.07	54	31.40	26.50	27.57
17	12.90	8.00	9.07	36	22.40	17.50	18.57	55	31.90	27.00	28.07
18	13.40	8.50	9.57	37	22.90	18.00	19.07	56	32.40	27.50	28.57
19	13.90	9.00	10.07	38	23.40	18.50	19.57	57	32.90	28.00	29.07
20	14.40	9.50	10.57	39	23.90	19.00	20.07	58	33.40	28.50	29.57
21	14.90	10.00	11.07	40	24.40	19.50	20.57	59	33.90	29.00	30.07
22	15.40	10.50	11.57	41	24.90	20.00	21.07	60	34.40	29.50	30.57

4	SOLDER TABS	PHOSPHOR BRONZE	MATTE Tin
3	CONTACT	PHOSPHOR BRONZE	MATTE Tin
2	COVER	LCP,94V-0	BLACK
1	HOUSING	LCP,94V-0	NATURE
NO.	PART NAME	MATERIAL	REMARK



SCALE: 1:1 UNIT: mm
SIZE: A4

Title: FPC 0.5 Pitch 90° SMT Type
H2.0mm connector

Unless otherwise
General Tolerance:
X ±0.40
X.x ±0.30
X.xx ±0.20
X* ±5°
X.x° ±3°

Molde Code: GT-F0506SR20-XXXXX01

DRAWN	CHECKED	APPROVED	DATE
Xia	Chen	Chen	2022.12.28



REV: A0 SHEET: 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [G-Switch](#) manufacturer:

Other Similar products are found below :

[00-6200-227-022-800](#) [006205250500825+](#) [006205280500825+](#) [FPH-1602G](#) [086222026001800](#) [52610-0675](#) [62674-201121DLF](#) [52746-1671-TR250](#) [10051922-1610EHLF](#) [10051922-2810EHLF](#) [686322124422](#) [XF3M-2915-1B-R100](#) [AYF353125A](#) [AYF530665TA](#) [AYF534065TA](#) [20FLH-RSM1-TB](#) [207356-1](#) [SFW12R-5STE9LF](#) [SFW18R-1STAE9LF](#) [SFW4R-5STE9LF](#) [52807-0430](#) [046283021002868+](#) [FFC05011-10SBB114W5M](#) [502250-8027](#) [67000-008LF](#) [200528-0260](#) [FH28K-10S-0.5SH](#) [FH52K-6S-0.5SH](#) [0.5K-DX-30PWB](#) [DS1020-08-10VBT12](#) [THD0515-34CL-GF](#) [X05A10L28G](#) [ECC2841061EU](#) [1.0K-DHQX-16PWB](#) [1.0K-DHQX-30PWB](#) [1775333-6](#) [10054365-202110ELF](#) [10054365-242110ELF](#) [10054365-282110ELF](#) [10064555-392220HLF](#) [59453-041110EBHLF](#) [59453-091110EDHLF](#) [62674-241141ALF](#) [62684-432100ALF](#) [62684-451100AHLF](#) [62684-5721N0ALF](#) [HFW11R-1STE1MTLF](#) [HFW12R-1STE9LF](#) [HFW14R-1STE9MTLF](#) [HFW18S-2STE9LF](#)