

CIRCUIT DIAGRAM



## GT-TC158X-HXXXXX-LX

### Operating Force

- A=160gf
- B=260gf
- C=100gf
- D=230gf

### Switch Height

- H0325=3.25mm
- H0375=3.75mm
- H0575=5.75mm
- H0875=8.75mm

### Switch Lifetime (Force)

L1=100,000 Cycles

### G-Switch Specification:

1. Operating temperature range: -40°C ~ +85°C
2. Rating: 50mA, 12V DC
3. Insulation resistance: 100MΩ min, 100V DC
4. Dielectric strength: 250V AC for 1 min
5. Contact resistance: 100mΩ max.
6. Travel: 0.30<sup>+0.1</sup><sub>-0.0</sub>mm
7. Waterproof grade: IPX7

SCALE: UNIT: mm

SIZE: A4

Unless otherwise  
General Tolerance:

X ±0.30  
X.X ±0.20  
X.XX ±0.15  
X.XXX ±0.10  
Angles ±3°

Title: Horizontal Tact Switch SMT

8.0×8.0×Hmm

Mold Code: GT-TC158X-HXXXXX-LX

DRAWN

CHECKED

APPROVED

DATE

Xia


Chen

Chen

2023.02.01

REV: A0

SHEET: 1/1



A

B

C

D

E

5

4

3

2

1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Tactile Switches](#) category:*

*Click to view products by [G-Switch](#) manufacturer:*

Other Similar products are found below :

[5GTH92001](#) [5GTH9202242](#) [6407-250V-25273P](#) [ADTSA62NV](#) [ADTSA62RV](#) [B3F-3123](#) [1977177-8](#) [1977266-1](#) [ADTSA63NV](#)  
[ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM32NVTR](#) [ADTSMW64RV](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [KSC241J SP DELTA LFS](#)  
[3FTL600RAS](#) [3FTL640RAS](#) [Y96K132V0FPLFS](#) [5GTH9658222](#) [ADTSM31NVTR](#) [2-1977120-7](#) [TSJW-5.2-260-TR](#) [KMT011MNGJLHS](#)  
[B3WN6002S](#) [70-201.0](#) [ADTSG648NV](#) [ADTSM62KSVTR](#) [ADTSM648NV](#) [95C06E3RAT](#) [5GTH96561](#) [3ATH9Q](#) [FSMRA8JHA04](#)  
[HARS0073](#) [Y33R411N9FPLFT](#) [Y31C01402FPLFS](#) [PTS645SK50SMTR92](#) [ADTSM32NVB](#) [KMS233GPWTLFG](#) [Y78B64124FP](#)  
[Y96D113G0FP LFS](#) [Y33A812C5FP LFT](#) [Y56B2D120FP LFS](#) [PTS645 DVM83-BN125-2 LFS](#) [B3W 1000G](#) [KSC621G OL LFS](#) [B3F 1002C](#)  
[B3F 0047H](#) [B3F 1000G](#) [B3W 1002C](#)