



GT-TD054X-HXXX-LX

Operating Force
 A=180gf
 B=250gf
 C=130gf

Switch Height
 H035=3.5mm

Switch lifetime (Force)
 L1=100,000 Cycles




P.C.B LAND DIMENSION



CIRCUIT DIAGRAM

- G-Switch Specification:**
1. Operating temperature range : -40 °C to +85 °C
 2. Rating : 50mA, 12V DC
 3. Insulation resistance : 100MΩ min, 100V DC
 4. Dielectric strength : 250V AC for 1 min
 5. Contact resistance : 100m Ω max.
 6. Travel : 0.25±0.1mm



SCALE: 1:1	UNIT: mm	Title: Horizontal Tact Switch 7.0x3.5x3.5mm		
SIZE: A4		Mold Code: GT-TD054X-H035-LX		
Unless otherwise General Tolerance:		DRAWN	CHECKED	APPROVED
X	±0.30	Xia	Chen	Chen
X.X	±0.20			
X.XX	±0.15			
X.XXX	±0.10			
X.XXXX	±3°			
Angles				



REV: A0 SHEET: 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tactile Switches](#) category:

Click to view products by [G-Switch](#) manufacturer:

Other Similar products are found below :

[5GTH92001](#) [5GTH9202242](#) [6407-250V-25273P](#) [ADTSA62NV](#) [ADTSA62RV](#) [B3F-3123](#) [1977177-8](#) [1977266-1](#) [ADTSA63NV](#)
[ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM32NVTR](#) [ADTSMW64RV](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [KSC241J SP DELTA LFS](#)
[3FTL600RAS](#) [3FTL640RAS](#) [Y96K132V0FPLFS](#) [5GTH9658222](#) [6407-250V-25343P](#) [ADTSM31NVTR](#) [2-1977120-7](#) [TSJW-5.2-260-TR](#)
[KMT011MNGJLHS](#) [B3WN6002S](#) [70-201.0](#) [ADTSG648NV](#) [ADTSM62KSVTR](#) [ADTSM648NV](#) [95C06E3RAT](#) [5GTH96561](#) [3ATH9Q](#)
[FSMRA8JHA04](#) [HARS0073](#) [Y97HS12A5RAFP](#) [Y97BT23B2HAFP](#) [Y33R411N9FPLFT](#) [Y31C01402FPLFS](#) [PTS645SK50SMTR92](#)
[ADTSM32NVB](#) [KMS233GPWTLFG](#) [Y78B64124FP](#) [PTS638SK25SMTR2LFS](#) [Y96D113G0FP LFS](#) [Y33A812C5FP LFT](#) [Y56B2D120FP](#)
[LFS](#) [PTS645 DVM83-BN125-2 LFS](#) [B3W 1000G](#) [KSC621G OL LFS](#)