



NOTE:

1. ELECTRICAL CHARACTERISTICS:

1.1 CONTACT RESISTANCE:

40mΩ Max FOR VBUS ,GNA AND OTHER CONTACTS
50mΩ CHANGE AFTER ENVIRONMENT TEST

1.2 CONTACT CURRENT RATING:

COLLECTIVELY VBUS PIN (A4,A9,B4,B9) ,TOTAL 5A
VCCON PIN (B5) THROUGH GND PIN(A1,A12,B1,B12),1.25A

OTHERS PIN, 0.25A

1.3 DIELECTRIC WITHSTANDING VOLTAGE: 100V AC (R.M.S).

1.4 INSULATION RESISTANCE 100MΩ Min.

2. MECHANICAL CHARACTERISTICS:

2.1 MATING FORCE: 5~20 N.

2.2 UNMATED FORCE: INITIAL 8~20N; 6~20N AFTER 10000 CYCLES

2.3 OPERATING TEMPERATURE: -40°C ~ 120°C

2.4 DURABILITY: 10,000 CYCLES

3. DIMENSIONS ARE IN MILLIMETERS

4. RECOMMENDED PROCESS: IR REFLOW 260°C ,5 ~ 10 SECONDS.

5. THE CONNECTOR IS ROHS/HALOGEN COMPLIANT.

6. THE PACKAGE IS TAPE & REEL

7. THE PART CONFORMS TO USB TYPE C SPEC UNLESS SPECIFIED

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
08 COVER	LCP		1	Black, UL94 V-0							
07 UNDER SHELL	SUS304		1	T=0.25, Solder area Plating Au 1U"							
06 OUTER SHELL	SUS304		1	T=0.25, Solder area Plating Au 1U"							
05 INNER SHELL	SUS304		1	T=0.30, Plating nickel							
04 MOLDING	LCP		1	Black, UL94 V-0							
03 SHIELDING PLATE	SUS301		1	T=0.15, Plating nickel							
02 BOTTOM CONTACT	Copper alloy		12	T=0.12, Au 30u", Plated at contact area, 1U" MIN plated at solder area.							
01 TOP CONTACT	Copper alloy		12	T=0.12 Au 30u", Plated at contact area, 1U" MIN plated at solder area.							
NO.	VARIETY	MATERIAL	QTY	REMARK							

品贊科技
b-Switch

Unless otherwise specified, Tolerance:
 X. ±0.30
 X.x ±0.20
 X.xx ±0.15
 X.xxx ±0.10
 Angles ±3°

G-Switch Electronic (HongKong) CO.,Ltd.

DESIGN LI Qingqi	DATE 2022.04.22	Molde code:	
CHECKED	DATE	GT-USB-7091A	
APPROVED	DATE		
http://www.dg-switch.com		REV.: X1	SCALE: 4:1
TEL:0769-82388879		UNIT: mm	
		SIZE: A4	SHEET: 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [G-Switch](#) manufacturer:

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [A-USB A-2P-C](#)
[MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [MUSBB151341](#)
[10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#) [UA-20BMFA-](#)
[SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#) [2274475-3](#) [UB-](#)
[20BMFA-SL8001](#) [UB-20PMFP-SC8003](#) [914-614A2025S10200](#)