



**PB-22E18-6PX**

X=NO LOCK  
L=LOCK

**G-Switch Specification:**  
 Electrical Specifications: 0.5A 30VDC  
 Contact Resistance : ≤100mΩ  
 Insulation Resistance: ≥100MΩ DC125V  
 Withstand Voltage: AC125V 1 minute  
 Operating Temperature: -25°C~+65°C  
 Storage Humidity: ≤85%RH  
 Electrical Life: 10,000  
 Mechanical Life: 100,000

注：“\*”表示关键尺寸(3个)。



**G-Switch** 品致科技

Unless otherwise specified, Tolerance:  
 X ±0.30  
 X.X ±0.20  
 X.XX ±0.15  
 X.XXX ±0.10  
 Angles ±3°

<b>G-Switch Electronic (HongKong) CO., Ltd.</b>	
DESIGN Bright Lee	DATE 2016.05.29
CHECKED	DATE
APPROVED	DATE
Mold code: PB-22E18-6PX	
http://www.dg-switch.com	
REV: X1	SCALE: 4:1
SIZE: A4	SHEET: 1/1
TEL:0769-82388879	UNIT: mm

**P.C.B LAYOUT  
BOTTOM VIEW**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [G-Switch](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE 01A](#)  
[MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#)  
[861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#)  
[A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#)  
[1211500044](#) [121194](#) [1212MRA](#) [1232A6NF](#) [1241.1183.7047](#) [121489](#) [1223A2ULCSA](#) [1241.1183.8000](#) [1241.1183.8029](#) [D5P-MT4](#)  
[13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#)