


P.C.B LAYOUT  
BOTTOM VIEW

**SCHEMATIC (NON-SHORTING)**



**PS-22E35XX**

PUSH SWITCH

G-Switch P/N


N=NO LOCK  
L=LOCK

- A=黑色
- B=红色
- C=蓝色
- D=其它

**G-Switch Specification:**

Electrical Specifications: 0.5A 30VDC  
 Contact Resistance:  $\leq 100m\Omega$   
 Insulation Resistance:  $\geq 100M\Omega$  DC125V  
 Withstand Voltage: AC125V 1 minute  
 Operating Temperature:  $-25^{\circ}C \sim +65^{\circ}C$   
 Storage Humidity:  $\leq 85\%RH$   
 Electrical Life: 10,000  
 Mechanical Life: 100,000

注：“\*”表示关键尺寸(7个).



Unless otherwise specified, Tolerance:		DESIGN Bright Lee		DATE 2016.05.29		Mold code:	
X	±0.30	CHECKED	DATE			PS-22E35	
X	±0.20	APPROVED	DATE			REV.: X1	SCALE: 4:1
X	±0.15	http://www.dg-switch.com		SIZE: A4	SHEET: 1/1	UNIT: mm	
X	±0.10	TEL:0769-82388879					
Angles	±3						

G-Switch Electronic (HongKong) CO.,Ltd.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [G-Switch](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE 01A](#)  
[MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#)  
[861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#)  
[A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#)  
[1211500044](#) [121194](#) [1212MRA](#) [1232A6NF](#) [1241.1183.7047](#) [121489](#) [1223A2ULCSA](#) [1241.1183.8000](#) [1241.1183.8029](#) [D5P-MT4](#)  
[13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#)