


P.C.B LAYOUT  
TOP VIEW

**SCHEMATIC (NON-SHORTING)**



**PS-22F27XX**



- A=黑色
- B=红色
- C=蓝色
- D=其它

**G-Switch Specification:**

Electrical Specifications: 0.5A 30VDC  
 Contact Resistance :  $\leq 100m\Omega$   
 Insulation Resistance:  $\geq 100M\Omega$  DC125V  
 Withstand Voltage: AC125V 1 minute  
 Operating Temperature: -25°C~+65°C  
 Storage Humidity:  $\leq 85\%RH$   
 Electrical Life: 10,000  
 Mechanical Life: 100,000



**G-Switch Electronic (HongKong) CO.,Ltd.**

Unless otherwise specified, Tolerance:	
X	$\pm 0.30$
X.X	$\pm 0.20$
X.XX	$\pm 0.15$
X.XXX	$\pm 0.10$
Angles	$\pm 3$

DESIGN	Bright Lee	DATE	2016.05.29	Mold code:	
CHECKED		DATE			
APPROVED		DATE			
				REV: X1	SCALE: 4:1
				SIZE: A4	SHEET: 1/1
				UNIT: mm	
				http://www.dg-switch.com	
				TEL:0769-82388879	

PS-22F27

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [G-Switch](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)