










PS-5824SVX-4PN

**PUSH SWITCH**

**Switch Type**
58=5.8×5.8mm

**Switch Height**
24=2.4mm

**Foot Type**
S=Smt

**Type**
V=Vertical

**Foot Position**
4P=4pin

**Operating Force**
A=180gf
B=250gf

**Switch Function**
L=Lock
N=No Lock







P.C.B LAYOUT




**PUSH-ON**:
1-3,4-6 Conduction
**PUSH-OFF**
No Conduction

SCHEMATIC




**G-Switch Specification:**
Operating temperature range：-40℃to+85℃
Rating：0.5A.24V DC
Insulation resistance:：100MΩ min.100V DC
Dielectric strength： 250V AC for 1 min
Contact resistance:：100m Ω max.
Switch lifetime：30,000Cycles

| NO. | PART NAME | MATERIAL | QTY | FINISHING |
|---|---|---|---|---|
| 8 | | | | |
| 7 | TERMINAL | BRASS | 6 | Ag PLATED |
| 6 | CASE | PPA | 1 | BLACK |
| 5 | LOCK PIN | SUS WIRE | 1 | NATURAL |
| 4 | SPRING | SUS WIRE | 1 | NATURAL |
| 3 | CONTACT | BRONZE | 2 | Ag PLATED |
| 2 | KNOB | PPA | 1 | WHITE |
| 1 | COVER | PPA | 1 | BLACK |

Pb Process Capable — RoHS Compliant 2002/95/EC — HALOGEN Compliant Halogen Free

品赞科技 G-Switch ®

Unless otherwise specified, Tolerance:

| | |
|---|---|
| X. | ±0.30 |
| X.x | ±0.20 |
| X.xx | ±0.15 |
| X.xxx | ±0.10 |
| Angles | ±3° |

G-Switch Electronic (HongKong) CO.,Ltd.

| | | | |
|---|---|---|---|
| DESIGN Feng² | DATE 2022.08.12 | Molde code: PS-5824SVX-4PN | |
| CHECKED | DATE | | |
| APPROVED | DATE | | |
| http://www.dg-switch.com | REV.: X1 | SCALE: 4:1 | UNIT: mm |
| TEL:0769-82388879 | SIZE: A4 | SHEET: 1/1 | |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** Pushbutton Switches ***category:***

***Click to view products by*** G-Switch ***manufacturer:***

Other Similar products are found below :

8971K1133 LW2L-M1C20M-A M22-D-R-GB0/K11 67021K512 701PB580 7199K101 810K12910 810KSV30B FLT 2U EE 01A MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 9533CD4+U574+U4922 99-450.837 99-453.837 A2PMA1X03EC56 A3A-7310 A3A-7340 12037A2ULCSA 1203A2UL ABGW410-R 1211390004 ABN400-R 121382 1213C3 HE3B-M2 1211500044 121194 1212MRA 1232A6NF 1241.1183.7047 121489 1223A2ULCSA 1241.1183.8000 1241.1183.8029 D5P-MT4 13435AG 13445AD29GX768 AG23-L2 AH165-2SGLG1TE3