


Quality Products. Service Excellence.

Type 4, 4X Mild Steel and Stainless Steel Base Units Series 2000

Modular Console System













Application

- Flexible design provides panel mount or rack mount capabilities for a variety of applications.
- Generally used in combination with other modular console components (ie. another base, terminal, desk and/or turret).
- · Available in either single or dual access format.
- Smooth lines and clean edges provide an attractive, contemporary appearance.

Standards

- UL 508A Type 3R, 4,12 (Stainless Steel, add 4X)
- CSA Type 3R, 4, 12, 13 (Stainless Steel, add 4X)
- EIA RS-310-E
- · Complies with
 - NEMA Type 3R, 4, 12 (Stainless Steel, add 4X)
 - o IEC 60529, IP66

Construction

- Formed 14 gauge steel bodies with 14 gauge steel door.
- Also offered with formed 14 gauge 304 stainless steel bodies with 14 gauge 304 stainless steel door.
- Smooth, continuously welded seams.
- · Body stiffeners are provided where required for increased strength and rigidity.
- Offered in 4 widths 24", 36", 48" and 60".
- Single access version has solid sides and back, solid door on front, open top, and closed bottom with removable access panel.
- Dual access version is same as above except has solid door on both front and back.
- 24" and 36" widths have single door on the front (and back for dual access) whereas 48" and 60" widths have two outside hinged doors on the front (and back for dual access).
- Doors can be hinged from either side on 24" and 36" units.
- Door profiles provide increased strength and are pre-punched to provide mounting options.
- Formed lip on enclosure excludes flowing liquids and contaminants.
- Slotted quarter turn oil-tight latches secure the door, with optional tamper resistant and locking latches available.
- Stainless steel models utilize stainless steel hardware.
- · Oil resistant gaskets are permanently secured.
- Features several internal stud locations for mounting of various accessories.
- A bonding screw is provided on the door and a grounding stud is provided in the enclosure.

Finish

- Available in RAL 7035 light gray textured powder coating and natural stainless steel with a smooth, brushed finish.
- Base Covers are available in the same finishes.

Gallery







Accessories

- S2000 Internal Components
- S2000 External Components
- Quarter Turn Inserts and Keys
- Climate Control
- General Accessories

- S2000 Rack Components
- Quarter Turn Assemblies
- Padlock Adaptor
- Lighting

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

Single Access

RAL 7035 Light	Stainless				
Gray	Steel	Enclosure			
Part No.	Part No.	Н	W	D	
2CLB262418	2CSB262418	26.00	24.00	17.30	
2CLB263618	2CSB263618	26.00	36.00	17.30	
2CLB264818	2CSB264818	26.00	48.00	17.30	
2CLB266018	2CSB266018	26.00	60.00	17.30	

Dual Access

RAL 7035 Light	Stainless				
Gray	Steel	Enclosure			
Part No.	Part No.	Н	W	D	
2CLBX262418	2CSBX262418	26.00	24.00	16.50	
2CLBX263618	2CSBX263618	26.00	36.00	16.50	
2CLBX264818	2CSBX264818	26.00	48.00	16.50	
2CLBX266018	2CSBX266018	26.00	60.00	16.50	

Data subject to change without notice

© 2021. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Racks & Rack Cabinets category:

Click to view products by Hammond manufacturer:

Other Similar products are found below:

1440-0131-78 1440-0132-78 1440-0133-36 AX103928 5231308-07 C2FSKBK1 UPS 525-17-9 PLAIN UPS 350-17-12 PLAIN UNC-3-7-5-PLAIN UNC-23/4-6-6-PLAIN SN8VCMW R4PCNWH R4P36WH NAKIT2.0G5-B SR14UBDP SR42UBDP48 SR48UBDP48 1440-0131-84 UPS 350 12-14 SEMI-GLOSS BLK UPH 350-12-14-BT UPR 525-17-14 BLU/WHT 1419976 RM1908BKVP RM2U19BKFP 1564A2BK1 895-39949 5231304-07 18P3317 18P4545 HCT302411H HCT362011H HCT363011H HCT363611H HCT482411H HCT483011H HCT483611H HCT484814H 1UHD722918N4SS RM3U19BKFP RM2U1918SBK 2CLD83643 2CLD84843 2CLT204843 RB-2PA1945NF RB-2PA1945BK RB-2PA2345NF RM4U1922SBK RM4U1918SBK SDC246U31BK SDC246U24BK