

Quality Products. Service Excellence.

Type 4, 4X Mild Steel and Stainless Steel Consolet Series 2000

Modular Console System















Application

- Serves as an economical housing for operator interface applications.
- Provides an ideal sloped surface for mounting keyboards, switches, indicator lights, and/or dials.
- Provides panel mounting capabilities for a variety of applications. Generally used as a stand alone enclosure. Possible to put side by side with base on a single plinth (ie. 36" wide consolet with 24" base with terminal all together on a 60" plinth.
- Optional casters (require plinth) allow for a completely mobile, NEMA rated work station.
- Smooth lines and clean edges provide an attractive, contemporary appearance.

Standards

- UL 508A Type 3R, 4,12 (Stainless Steel, add 4X)
- CSA Type 3R, 4, 12, 13 (Stainless Steel, add 4X)
- EIA RS-310-E
- Complies with
 - NEMA Type 3R, 4, 12 (Stainless Steel, add 4X)
 - IEC 60529, IP66

Construction

- Formed 14 gauge steel bodies with 14 gauge steel door and lid.
- Also offered with formed 14 gauge 304 stainless steel bodies with 14 gauge 304 stainless steel door and lid.
- Smooth, continuously welded seams without knockouts or holes.
- · Body stiffeners are provided where required for increased strength and rigidity.
- Offered in 4 widths 24", 36", 48" and 60".
- Has solid sides and back, solid door on front, 3 point adjustable lid on sloped (20°) top, and closed bottom with removable access panel.
- 24" and 36" widths have single door on the front whereas 48" and 60" widths have two outside hinged doors on the front.
- Doors can be hinged from either side on 24" and 36" units.
- Door profiles provide increased strength and are pre-punched to provide mounting options.
- Formed lip on enclosure excludes flowing liquids and contaminants.
- Slotted quarter turn oil-tight latches secure the door and lid, with optional tamper resistant and locking latches available.
- Stainless steel models utilize stainless steel hardware.
- Oil resistant gaskets are permanently secured.
- Features internal stud locations for mounting optional inner panel.
- A bonding screw is provided on the door and a grounding stud is provided in the enclosure.

Finish

• Available in RAL 7035 light gray textured powder coating and natural stainless steel with a smooth, brushed finish.

Accessories

- Consolet Panel
- Quarter Turn Inserts and Keys
- Footrest
- Padlock Adaptor
- General Accessories

- Quarter Turn Assemblies
- Modular Plinth
- Climate Control
- Lighting

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

RAL 7035 Light	Stainless				
Gray	Steel	Enclosure			
Part No.	Part No.	H1	H2	W	D
2CLC2024	2CSC2024	30.36	38.03	24.00	17.30
2CLC2036	2CSC2036	30.36	38.03	36.00	17.30
2CLC2048	2CSC2048	30.36	38.03	48.00	17.30
2CLC2060	2CSC2060	30.36	38.03	60.00	17.30

Data subject to change without notice

© 2021. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Racks & Rack Cabinets category:

Click to view products by Hammond manufacturer:

Other Similar products are found below :

 1440-0131-78
 1440-0132-78
 1440-0133-36
 AX103928
 5231308-07
 C2FSKBK1
 UPS 525-17-9
 PLAIN
 UPS 350-17-12
 PLAIN
 UNC-3-7-5

 PLAIN
 UNC-23/4-6-6-PLAIN
 SN8VCMW
 NAKIT2.0G5-B
 SR14UBDP
 SR42UBDP48
 1440-0131-84
 UPS 350-12-14
 SEMI-GLOSS
 BLK

 UPH 350-12-14-BT
 UPR 525-17-14
 BLU/WHT
 RM1908BKVP
 RM2U19BKFP
 1564A2BK1
 895-39949
 5231304-07
 18P3317
 18P4545

 HCT302411H
 HCT362011H
 HCT363011H
 HCT482411H
 HCT483011H
 HCT484814H
 1UHD722918N4SS

 RM3U19BKFP
 RM2U1918SBK
 2CLD83643
 2CLD84843
 RB-2PA1945NF
 RB-2PA1945BK
 RB-2PA2345NF

 RM4U1922SBK
 RM4U1918SBK
 SDC246U31BK
 SDC246U24BK
 SDC243U31BK
 SDC243U24BK