

Quality Products. Service Excellence.

Seismic 2-Post Open Frame Rack DRZ4 Series

UL2416 rated for up to 2,000 lbs (907 kg). Static Load tested to 8,000 lbs (3,628 kg). Seismic rated for up to 800 lbs (362 kg)

















Features

- Rugged design was engineered to perform in the most critical seismic environments.
- Increased overall width of 22.75 inches provides additional side-to-side load strength.
- EIA compliant 10-32 front and rear tapped (6.00" deep) rails with 19" mounting.
 - · Includes marked rack unit dividers to aid in equipment mounting.
- Two (2) sets of side mounting holes on side of rack allows for Hammond cable managers to be mounted facing front and rear.
- The side mounting holes can also be used to gang racks together.
- Includes two (2) pairs of integrated 10-32 ground studs, spaced 5/8" apart. Stud pairs are
 located conveniently at both ends of the rack. The upper location is centered inside the
 upper channel and the lower location is centered on the front base of the rack. This
 upgrade ensures a secure and easy ground lug attachment.
- Includes top bracket mounting holes that are compatible with top cable accessories.
- Includes large base for freestanding support of equipment.
- · Finished in smooth black powder paint.

Specifications

- Constructed in 10-gauge steel (rails) reinforced with structural angle base for maximum structure.
- UL Listed 2416 load rated for up to 2,000 lbs (907 kg). Static Load tested to 8,000 lbs (3,628 kg)
- Dynamic (seismic) load rated for up to 800 lbs (362 kg) of equipment installed and 50 lbs (22 kg) of cable weight. Requires a seismic bolt down kit such as the C4K-Z4 (sold separately). Independently tested and certified to exceed established Seismic Zone 4 NEBSTM Telcordia® GR-63-CORE testing standards.
- TAA compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.



Looking for a Seismic 4-Post Open Frame Rack? See our RAAB Series for more information.

Accessories

- High-Density Vertical Finger Manager with Slam-Latching Door
- Vertical Rack Cable Manager with Door
- Horizontal Finger Cable Manager
- Two Post Mounting Adjustable Shelf
- Two Post Centered Shelf
- Two Post Heavy Duty Battery Shelf
- · Grounding & Bonding

- Vertical Finger Cable Manager with Door
- Horizontal Ring Cable Manager
- Universal Rack Shelf
- Two Post Variable Depth Shelf
- Two Post Mounting Keyboard & Equipment Shelf
- Two-Post Extension Support Bracket
- 10-32 Mounting Hardware

• PDUs and Outlet Strips







	Ove	Overall Dimensions			Mounting Dimensions			Rack Unit
Part No.	Height	Width	Depth	Units	Height	Width	Depth	Indicator
DRZ477	84.00	22.75	18.00	44U	77.12	19.00	6.00	Hole Indicator
DRZ477S	84.00	22.75	18.00	44U	77.12	19.00	6.00	Numbered 1-44
DRZ42377	84.00	26.75	18.00	44U	77.12	23.00	6.00	Hole Indicator

⁴⁻Post Rack option also available.

Rack Isolation Kit for DRZ4

	Overa	III Dimensions		Quantity Included		
Part No.	Thickness	Width	Depth	Isolation Pads	Shoulder Washers	
RIK19Z4	0.06	20.00	7.50	2	4	
RIK23Z4	0.06	24.00	7.50	2	4	

Tags: Relay Rack, H-Frame, Server Rack, Equipment Rack, Network Rack, Skeleton Rack, Telco Rack, Data subject to change without notice Two-Post Rack, sismic

© 2021. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Racks & Rack Cabinets category:

Click to view products by Hammond manufacturer:

Other Similar products are found below:

1440-0133-36 5231308-07 UPS 525-17-9 PLAIN UPR-525-17-12 BLU/WHT UPR 525-17-14 BLU/WHT 7709.735 RM2U19BKFP UPS 350-17-12-BLUE/WHITE UPS 350-17-9-BLUE/WHITE DN-WD19 12U/600 5231304-07 RM3U19BKFP RM2U1918SBK UPS 525-14-7-BLUE/WHITE 24563-132 24563-142 24563-142 24563-143 24563-144 24563-194 24563-191 24563-431 24563-432 UPS 525-17-9-BLUE/WHITE RB-2PA1945NF RB-2PA1945BK RM4U1922SBK RM1U1922SBK HDR6UBK RM1UMTGFL DN-W19 06U/450 DN-W19 09U/450 DN-W19 12U/450 G17083UBK P32180011 P32180012 P32180031 433496D 24563-157 G17081UG G17083UG 60-2313-GT ARR-1272-NF ARR-1276-NF ARR-1294-NF BRP-12202 BRP-12206 BRP-12212 BRP-12218 CH-14403