Quality Products. Service Excellence.

Type 4 Mild Steel Wallmount Disconnect Enclosure Eclipse Series

Hinge Door with Handle (Flange w/ multi-vendor cutout)



Panel Sold Separately











Application

- Designed to house the following safety disconnect equipment:
 - ABB Controls flange mounted variable depth operating mechanisms for disconnect switches and circuit breakers. Cable version for circuit breakers also available.
 - Allen Bradley 1494V and 1494U variable depth flange mounted disconnect switches and circuit breaker mechanisms.
 - Cutler Hammer C361 variable depth flange mounted disconnect switches and C371 circuit breaker operators. Also Flex-Shaft[™] handle mechanisms for circuit breakers. Use Cutler Hammer NEMA 4X rated operating handles to maintain NEMA 4X integrity.
 - Siemens I-T-E Max-Flex[™] flange mounted variable depth handles for disconnect switch and circuit breakers. Use handle for NEMA 4 rating.
 - General Electric Type STDA flange handles and variable depth operating mechanisms for disconnect switches and circuit breakers. Also SpectraFlex™ cable operators for circuit breakers.
 - Square D Class 9422 disconnect switches with flange mounted variable depth operating mechanisms or cable mechanisms and Class 9422 flange mounted variable depth operating mechanism or cable mechanisms for circuit breakers. SN4SS enclosures will not accept Square D Class 9422 bracket-mounted disconnect devices, 9422TG1 or TG2 devices.
- · Refer to the Type 4 Wallmount Selection Guide.

Standards

- UL 508A Type 3R, 4
- CSA Type 3R, 4
- Complies with
 - o NEMA Type 3R, 4, 12 and 13
 - o IEC 60529, IP66
- Appropriate components are required to maintain these standards.

Construction

- Formed 14 gauge doors with 16 or 14 (36x32" and larger) gauge steel.
- · Continuously welded seams.
- · Larger sizes include door stiffeners.
- Formed lip on door and enclosure exclude flowing liquids and contaminants.
- Cutouts and holes are provided to suit the flange handle operating mechanism.
- Doors may be easily removed for modifications and are interchangeable.
- Door is secured with easily operated 2 or 3-point handle.
- · Cover interlock bracket is included on the door.
- Collar studs are provided for mounting inner panels.
- · Removable inner panel is sold separately.
- · Seamless poured-in place gasket.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure

- Includes hardware kit with panel mounting nuts and sealing washers for wall mounting holes.
- Disconnects and operating mechanisms are not provided with the enclosure, and must be ordered separately from the manufacturer.

Finish

• Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.

Accessories

- Additional Inner Panels
- Mounting Foot Kit
- Window Kits
- Lighting

- Door Stop Kit
- Drip Shield Kit
- Climate Control
- · General Accessories

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

	Enclosure			Optional Inner Panel		
Part No.	Н	W	D	Part No.	Н	W
EN4DSC20228GY	20.00	22.00	8.00	EP2020	18.17	18.17
EN4DSC24228GY	24.00	22.00	8.00	EP2420	22.17	18.17
EN4DSC24268GY	24.00	26.00	8.00	EP2424	22.17	22.17
EN4DSC30268GY	30.00	26.00	8.00	EP3024	28.17	22.17
EN4DSC36268GY	36.00	26.00	8.00	EP3624	34.17	22.17
EN4DSC36328GY	36.00	32.00	8.00	EP3630	34.17	28.17
EN4DSC423212GY	42.00	32.00	12.00	EP4230	40.17	28.17
EN4DSC423812GY	42.00	38.00	12.00	EP4236	40.17	34.17
EN4DSC483812GY	48.00	38.00	12.00	EP4836	46.17	34.17
EN4DSC603812GY	60.00	38.00	12.00	EP6036	58.17	34.17

Alternative inner panel options also available.

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Electrical Enclosures category:

Click to view products by Hammond manufacturer:

Other Similar products are found below:

MR-25L+ 1584DMGPK 30-8739 PIP-11774SCREW 30-9715 30-9777-BU 110-402 A242012LP A16N12BLP 111-005 9511096 9511016
9822011 CAB PC 203018 G NSYTLEU PC 30/25-FC3 9820006 1010.600 1012.600 AR242410CHSSL 120-404 127-406 127-906
79021101 EKIV 17 EKIV 37 18200101 18600801 19501001 19600901 TRH 24 A317SEAL A3735SEAL HV 60 MW X16C LGR-TR
X25C LGR-TR T 160 OE HD LGR T 350 OE HD LGR T 60 M20 T 60 M20 NL SDB 03 PS SDB 09 PS P2018SEAL EN1309N4
EN1511N4LATCH GSV171 2762-00 2763-00 2765-00 2761-00