



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material:PA66,UL94V-0

孔位 Poles	尺寸 (mm)			
	A	B	C	D
2	1.25	2.00	3.75	_____
3	2.50	3.20	5.00	_____
4	3.75	4.00	6.25	_____
5	5.00	4.00	7.50	_____
6	6.25	6.25	8.75	_____
7	7.50	6.25	10.00	_____
8	8.75	6.25	11.25	8.75
9	10.00	6.25	12.50	9.75
10	11.25	8.20	13.75	11.00
11	12.50	8.20	15.00	11.00
12	13.75	8.20	16.25	11.00
13	15.00	8.20	17.50	11.00
14	16.25	8.20	18.75	11.00
15	17.50	8.20	20.00	11.00

1251H-XXP	PA66 UL94V-0	1251W	1251T
PART NO	Material	Suitable Wafer	Suitable Terminal

—		new		2015/5/3		A		瀚源		
ECN BO.		DESCRIPTION.		DATE.		REV.				
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1				
Mikey	Tom	Jerry	PART NAME	1251H-XXP	UNLESS OTHERWISE SPECIFIED,TOLERANCE:	X.	±0.25			
			MODEL NAME	H-1251H-XXP		X.x	±0.20			
			3RD ANGLE PROJ	HanElectricity Co.,LTD		X.xx	±0.15			
			FILE.NO.							

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HanElectricity](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)