



适应基板厚度: 1.2mm~1.6mm
 温度范围: $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$
 额定电压: 250V AC/DC
 额定电流: 1A
 绝缘电阻: $\geq 1000\text{M}\Omega$
 耐压: 800V AC/minute

15	23	21.00	24.00
14	21.5	19.50	22.50
13	20	18.00	21.00
12	18.5	16.50	19.50
11	17	15.00	18.00
10	15.5	13.50	16.50
9	14	12.00	15.00
8	12.5	10.50	13.50
7	11	9.00	12.00
6	9.5	7.50	10.50
5	8	6.00	9.00
4	7.5	4.50	7.50
3	6	3.00	6.00
2	4.5	1.50	4.50
Pin	DIM.A	DIM.B	DIM.C

1502H-XXP	PA66 UL94V-0	1502W	1502T
PART NO	Material	Suitable Wafer	Suitable Terminal

—		new		2015/5/3		A		瀚源		
ECN BO.		DESCRIPTION.		DATE.		REV.				
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1				
Mikey	Tom	Jerry	PART NAME	1502H-XXP	UNLESS OTHERWISE SPECIFIED, TOLERANCE:		X.	± 0.25		
			MODEL NAME	H-1502H-XXP			X.x	± 0.20		
			3RD ANGLE PROJ	HanElectricity Co.,LTD		X.xx	± 0.15	ANGULAR	$\pm 3^{\circ}$	
				FILE.NO.						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HanElectricity](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)