



孔位	A	B
2	7.5	2.5
3	10.0	5.0
4	12.5	7.5
5	15.0	10.0
6	17.5	12.5
7	20.0	15.0
8	22.5	17.5
9	25.0	20.0
10	27.5	22.5
11	30.0	25.0
12	32.5	27.5
13	35.0	30.0
14	37.5	32.5
15	40.0	35.0
16	42.5	37.5

范围	>0-3	>3-18	>18-50	>50-100
公差	±0.15	±0.2	±0.3	±0.5

2508WV-XXP	PA66 UL94V-0	2508H	2508T
PART NO	Material	Suitable Housing	Suitable Terminal

- 使用温度范围 (Ambient temperature Range) : -25°~+85°
- 适用线规 (Applicable Wires) : AWG 28#~22#
- 适用基板厚度 (Applicable PCboard thickness) : 0.8mm~1.6mm
- 额定电压 (Voltage rating) : 250V AC,DC
- 额定电流 (Current rating) : 3A
- 额定电阻 (Contact Resistance) : <0.01Ω
- 绝缘电阻 (Insulation Resistance) : >1000MΩ
- 耐压 (Withstand Voltage) : 800V/min
- 材料 (Material)
 - 1 基座: PA66 94V-0
 - 2 插针: 黄铜

DESIGNED		CHECKED		APPROVAL		DRAWING NUMBER		DATE		REV.		SCALE	
Mikey		Tom		Jerry		PART NAME		2508WV-XXP		UNLESS OTHERWISE SPECIFIED, TOLERANCE		X. ±0.25 X.x ±0.20 X.xx ±0.15 ANGULAR ±3°	
						MODEL NAME		H-2508WV-XXP		HanElectricity Co., LTD.		FILE NO.	
						3RD ANGLE PROJ							

瀚源

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HanElectricity](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)