



P. C. B Layout

一. 电气性能:

1-1. 额定电流: 3A AC DC.

1-2. 接触电阻:  $\leq 20m\Omega$

1-3. 绝缘电阻:  $\geq 1000M\Omega$

1-4. 耐 压: 550V AC/Minute

二. 物理特性:

2-1. 操作温度:  $-55^{\circ}C \sim 105^{\circ}C$

2-2. 焊接温度:  $+220^{\circ}C$ , 10s max

三. 材质:

3-1. 塑胶: PBT(Black) UL94V-0

3-2. 插针: Brass/Gold plated

| PIN | A      | B     |
|-----|--------|-------|
| 1   | 2.54   | 0.00  |
| 2   | 5.08   | 2.54  |
| 3   | 7.62   | 5.08  |
| 4   | 10.16  | 7.62  |
| 5   | 12.70  | 10.16 |
| 6   | 15.24  | 12.70 |
| 7   | 17.78  | 15.24 |
| 8   | 20.32  | 17.78 |
| 9   | 22.86  | 20.32 |
| 10  | 25.40  | 22.86 |
| 11  | 27.94  | 25.40 |
| 12  | 30.48  | 27.94 |
| 13  | 33.02  | 30.48 |
| 14  | 35.56  | 33.02 |
| 15  | 38.10  | 35.56 |
| 16  | 40.64  | 38.10 |
| 17  | 43.18  | 40.64 |
| 18  | 45.72  | 43.18 |
| 19  | 48.26  | 45.72 |
| 20  | 50.80  | 48.26 |
| 21  | 53.34  | 50.80 |
| 22  | 55.88  | 53.34 |
| 23  | 58.42  | 55.88 |
| 24  | 60.96  | 58.42 |
| 25  | 63.50  | 60.96 |
| 26  | 66.04  | 63.50 |
| 27  | 68.58  | 66.04 |
| 28  | 71.12  | 68.58 |
| 29  | 73.66  | 71.12 |
| 30  | 76.20  | 73.66 |
| 31  | 78.74  | 76.20 |
| 32  | 81.28  | 78.74 |
| 33  | 83.82  | 81.28 |
| 34  | 86.36  | 83.82 |
| 35  | 88.90  | 86.36 |
| 36  | 91.44  | 88.90 |
| 37  | 93.98  | 91.44 |
| 38  | 96.52  | 93.98 |
| 39  | 99.06  | 96.52 |
| 40  | 101.60 | 99.06 |

| DESIGNED       |  | CHECKED                |  | APPROVAL                              |  | DRAWING NUMBER            |  | DATE       |  | REV.       |  | SCALE       |  |
|----------------|--|------------------------|--|---------------------------------------|--|---------------------------|--|------------|--|------------|--|-------------|--|
| Mikey          |  | Tom                    |  | Jerry                                 |  | PART NAME<br>2541WV-2xXXP |  | 2015/5/3   |  | A          |  | SCALE: 1/2  |  |
| 3RD ANGLE PROJ |  | HanElectricity Co.,LTD |  | UNLESS OTHERWISE SPECIFIED,TOLERANCE: |  | X ±0.25                   |  | X.x ±0.20  |  | X.xx ±0.15 |  | ANGULAR ±3' |  |
| ECN BO.        |  | DESCRIPTION.           |  | DATE.                                 |  | REV.                      |  | SCALE: 3:1 |  | SCALE: 3:1 |  | FILE. NO.   |  |

瀚源

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HanElectricity](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)