



使用温度范围 (Ambient temperature Range): $-25^{\circ}\sim+85^{\circ}$	孔位	A	B
适用线规 (Applicable Wires):AWG 28#~20#	2	0	5.4
适用基板厚度 Applicable PCboard thickness):1.7mm	4	4.2	9.6
额定电压 (Voltage rating):300V AC,DC	6	8.4	13.8
额定电流 (Current rating):4A	8	12.6	18.0
接触电阻 Contact Resistance): $<0.015\Omega$	10	16.8	22.2
绝缘电阻 (Insulation Resistance): $>1000M\Omega$	12	21.0	26.4
耐压 (Withstand Voltage):1000V/min	14	25.2	30.6
材料 (Material)	16	29.4	34.8
1.基座: PA66 FV2	18	33.6	39.0
2.插针: 黄铜	20	37.8	43.2
	22	42.0	47.4
	24	46.2	51.6

9357WV-2XXP	PA66 UL94V-0	9357H	9357T
PART NO	Material	Suitable Housing	Suitable Terminal

—		new		2015/5/3		A		瀚源	
ECN BO.		DESCRIPTION.		DATE.		REV.			
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1			
Mikey	Tom	Jerry	PART NAME	9357WV-2XXP	UNLESS OTHERWISE SPECIFIED,TOLERANCE:	X.	± 0.25		
			MODEL NAME	H-9357WV-2XXP		X.x	± 0.20		
			3RD ANGLE PROJ	HanElectricity Co.,LTD				X.xx	± 0.15
			FILE.NO.						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HanElectricity](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)