




| REV. | EC# | DESCRIPTION | DATE       | DRAWN | CHECK | APPROVED |
|------|-----|-------------|------------|-------|-------|----------|
| 1.00 |     | 初版发行        | 2020-05-28 |       |       |          |
|      |     |             |            |       |       |          |

| REV. | EC# | DESCRIPTION | DATE | DRAWN | CHECK | APPROVED |
|------|-----|-------------|------|-------|-------|----------|
|      |     |             |      |       |       |          |

|                |       |        |
|----------------|-------|--------|
| 10P            | 35.64 | 39.88  |
| 8P             | 27.72 | 31.96  |
| 7P             | 23.76 | 28     |
| 6P             | 19.8  | 24.04  |
| 5P             | 15.84 | 20.08  |
| 4P             | 11.88 | 16.12  |
| 3P             | 7.92  | 12.16  |
| 2P             | 3.96  | 8.2    |
| NUMBER OF PINS |       | DIM. A |
|                |       | DIM. B |



适用线规: AWG 26#~18#  
 温度范围: -25℃~85℃  
 额定电压: 250V AC/DC  
 额定电流: 7A  
 接触电阻: ≤0.01Ω  
 绝缘电阻: ≥1000MΩ  
 耐压: 1500V AC/minute

- 技术要求:
- 1) 材质: 见附表;
  - 2) 电镀: 见附表;
  - 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象;
  - 4) 端子表面无氧化、电镀不良等现象。

| 1   | Housing | 1 PCS | 材质: PA66 (UL94V-0) 颜色: 本色 |
|-----|---------|-------|---------------------------|
| NO. | NAME    | Q' TY | DESCRIPTION               |

|                  |     |            |         |                |            |            |
|------------------|-----|------------|---------|----------------|------------|------------|
| DRAW :           | 黄彬  | 2020-05-28 | TITLE:  | HX CH3. 96-10P | DRAW NAME: | 压线端子胶壳     |
| DESIGN:          | 张伟  | 2020-05-28 | SERIES: | 1501 SERIES    | DRAW NO.   |            |
| CHECK:           | 罗小春 | 2018-05-28 | P/N:    |                | UNIT:      | SHEET: 1/1 |
| APPROVED         |     |            | REV.    | 1.00           | SCALE      | N/A        |
| CUSTOMER DRAWING |     |            |         |                |            |            |

| GENERAL TOLERANCES |       |        |
|--------------------|-------|--------|
| DIM                | TOL   | DEG    |
| X.                 | ±0.15 | ±1.00° |
| X.X                | ±0.25 | ±2.00° |
| X.XX               | ±0.35 | ±3.00° |
| X.XXX              | ±0.50 | ±4.00° |

**深圳市韩下电子有限公司**  
 HANXIA ELECTRONICS CO., LTD.



深圳市韩下电子有限公司

Shenzhen Hanxia Electronic Co., Ltd  
Tel: 0755-33819206 Fax: 0755-27597491

## 承 认 书

### SPECIFICATION FOR APPROVAL

客 户 Customer:

\_\_\_\_\_

产品名称 Project:

**压线端子胶壳**

规格型号 Part No:

**HX CH3.96-10P**

#### 贵公司承认印 Approval signatures

| 料 号/Part No. | 签 章/Signatures |
|--------------|----------------|
|              |                |

日期 Date:

|             |     |  |
|-------------|-----|--|
| 拟制/Drawn    | 黄彬  |  |
| 审核/Check    | 张伟  |  |
| 批准/Approved | 罗小春 |  |

## 1、SCOPE: (适用范围)

1.1 This specification covers production and inspection of Connector.

本规范内容适用于本公司普通系列型条形连接器（针座）产品的生产与检验。

## 2、USE CONDITION: (使用条件)

2.1 Ambient temperature Range:-25℃~+85℃

环境温度：-25℃~+85℃

2.2 Applicable Wire Sizes:AWG#26~#18

适用线规： AWG#26~#18

2.3 Applicable PC board thickness:1.2~1.6mm

适用 PC 板厚度： 1.2~1.6 mm

## 3、Appearance and Dimension: (外观及尺寸)

3.1 Appearance:Product surface without defect、dirt、crack、and mechanical damang, Contact without rust,plating not oxidized and not peeled.

产品表面不应有对制品有害的缺陷、污垢、裂痕及机械损伤；接触件无锈蚀、镀层氧化、脱落等现象。

3.2 Dimension:According to drawings

外形尺寸：依照附图

3.3 Exchangable:Exchangable with same specification products.

互换性：相同规格应能互换

## 4、Material:

材料 (以图纸为准)

| P/N<br>零件名称                   | Type<br>类型         | Material<br>材料                   | Finish<br>表面处理                          | Explain<br>说明     |
|-------------------------------|--------------------|----------------------------------|---|-------------------|
| Terminal<br>端子                | Contact<br>插簧      | Phosphor bronze<br>锡青磷铜 厚 0.15mm | Tin Plating:3~4 μ m<br>镀锡: 3~4 μ m      | RoHS<br>Compliant |
| Housing<br>孔座                 | Plastic<br>塑壳      | Nylon66 UL94V-0                  | Color:White<br>颜色: 白色                   |                   |
| Opening Wafer<br>开口针座         | Contact<br>插针      | Phosphor bronze<br>锡青磷铜 厚 0.30mm | Tin Plating:3~4 μ m<br>镀锡: 3~4 μ m      |                   |
|                               | Plastic<br>塑壳      | Nylon46 UL94V-0                  | Color: Beige<br>颜色: 米色                  |                   |
| Lips Wafer<br>闭口针座            | Contact<br>插针      | Phosphor bronze<br>锡青磷铜 厚 0.30mm | Gold Plating:3~4 μ " m<br>镀金: 3~4 μ " m |                   |
|                               | Plastic<br>塑壳      | PBT UL94V-0                      | Color: White<br>颜色: 白色                  |                   |
| Tiepian Wafer<br>卧贴针座<br>立贴针座 | Contact<br>插针      | Phosphor bronze<br>锡青磷铜 厚 0.30mm | Tin Plating:3~4 μ m<br>镀锡: 3~4 μ m      |                   |
|                               | Solder tabs<br>焊护耳 | Phosphor bronze<br>锡青磷铜 厚 0.25mm | Tin Plating:3~4 μ m<br>镀锡: 3~4 μ m      |                   |
|                               | Plastic<br>塑壳      | Nylon46 UL94V-0                  | Color: Beige<br>颜色: 米色                  |                   |

## 5、Electrical Performance:

电气性能

| N0.<br>序号 | Ltem<br>项目                    | Requirement<br>技术要求    |
|-----------|-------------------------------|------------------------|
| 5.1       | Voltage Rated<br>额定电压         | 250V AC DC             |
| 5.2       | Current Rated<br>额定电流         | 7A AC DC               |
| 5.3       | Contact Resistance<br>接触电阻    | $\leq 0.01 \Omega$     |
| 5.4       | Insulation Resistance<br>绝缘电阻 | $\geq 1000 M\Omega$    |
| 5.5       | Dielectric Strength<br>耐压     | $\geq 1500V$ AC/minute |

## 6、Mechanical Performance:

机械性能

| N0.<br>序号 | Ltem<br>项目                               | Requirement<br>技术要求 |
|-----------|--|---------------------|
| 6.1       | Male contact Retention force<br>PIN 针固定力 | $\geq 25N$ per pin  |
| 6.2       | Female contact Retention force<br>端子固定力  | $\geq 25N$ per pin  |
| 6.3       | Plug-in force<br>插入力                     | $\leq 10N$ per pin  |
| 6.4       | Plug-out force<br>拔出力                    | $\geq 2N$ per pin   |

## 7、Endurance Characteristics:

环境性能

| N0.<br>序号 | Ltem<br>项目            | Requirement<br>技术要求  |
|-----------|-----------------------|--|
| 7.1       | Soldering rest<br>可焊性 | Time: $2.5 \pm 0.5S$<br>时间: $2.5 \pm 0.5S$<br><br>Temperature: $260 \pm 5^\circ C$<br>温度: $260 \pm 5^\circ C$<br><br>Area of Soldering: $\geq 95\%$<br>焊锡面积: $\geq 95\%$ |

|     |                                      |  |
|-----|--------------------------------------|--|
| 7.2 | Resistance to soldering Heat<br>耐焊接热 | <p>Time: 5 ± 1S<br/>时间: 5 ± 1S</p> <p>Temperature: 260 ± 5°C<br/>温度: 260 ± 5°C</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p>  |
| 7.3 | Heat test<br>耐热性                     | <p>Time: 96h<br/>时间: 96 小时</p> <p>Temperature: +85 ± 3°C<br/>温度: +85 ± 3°C</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p> <p>Contact resistance: ≤ 20 mΩ<br/>接触电阻: ≤ 20 mΩ</p>   |
| 7.4 | Cold test<br>耐冷性                     | <p>Time: 48h<br/>时间: 48 小时</p> <p>Temperature: -25 ± 3°C<br/>温度: -25 ± 3°C</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p> <p>Contact resistance: ≤ 20 mΩ<br/>接触电阻: ≤ 20 mΩ</p>   |
| 7.5 | Temperature Cycling<br>温度循环          | <p>Low temperature: -25 ± 3°C<br/>低温: -25 ± 3°C</p> <p>High temperature: 85 ± 3°C<br/>高温: 85 ± 3°C</p> <p>For 5 cycles. test after keeping in Normal Condition for 30 min.<br/>5 次循环后, 放置在正常环境中 30 分钟, 在进行测试</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p> <p>Contact resistance: ≤ 20 mΩ<br/>接触电阻: ≤ 20 mΩ</p> |

|     |                                |  |
|-----|--------------------------------|--|
| 7.6 | Invariablenes humidity<br>恒定湿热 | <p>Temperature: <math>60 \pm 2^{\circ}\text{C}</math><br/>温度: <math>60 \pm 2^{\circ}\text{C}</math></p> <p>Relative humidity: 90%-96% RH<br/>相对湿度: 90%-96% RH</p> <p>Tim: 96h<br/>时间: 96 小时</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p> <p>Contact resistance: <math>\leq 20 \text{ m}\Omega</math><br/>接触电阻: <math>\leq 20 \text{ m}\Omega</math></p> <p>Insulation Resistance: <math>\geq 100 \text{ M}\Omega</math><br/>绝缘电阻: <math>\geq 100 \text{ M}\Omega</math></p>  |
| 7.7 | Salt Spray<br>盐雾试验             | <p>Salt concentration: <math>5 \pm 1\%</math><br/>浓度: <math>5 \pm 1\%</math></p> <p>Temperature: <math>35 \pm 2^{\circ}\text{C}</math><br/>温度: <math>35 \pm 2^{\circ}\text{C}</math></p> <p>Tim: <math>16 \pm 2\text{h}</math><br/>时间: <math>16 \pm 2</math> 小时</p> <p>After salt is removed by running wafer and A drop is removed ,it is measured.</p> <p>把试验样品从试验箱顶悬挂下来, 采用浓度(<math>5 \pm 1</math>) %的氯化钠溶液, 连续雾化 16 小时, 试验后用流动的蒸馏水轻轻洗去表面沉积物, 在常温常驻湿条件下恢复 1-2 小时, 外观无损伤</p> <p>Appearance: NO Damage<br/>外观: 无损坏</p> <p>Contact resistance: <math>\leq 20 \text{ m}\Omega</math><br/>接触电阻: <math>\leq 20 \text{ m}\Omega</math></p> |



## 8、 Packaging Transportation Storage

包装、运输、贮存

### 8.1 Packaging

包装

- (1) **The packing of plastic inner is the plastic bag,the packing of inner terminal is panel mounting attach material packing, marked with product name, specification model, quantity, date in produced.**

塑件内包装为塑料袋， 端子内包装为盘装带料包装， 装（贴）入合格证， 注明产品名称、规格型号、数量生产日期

- (2) **Exterior package is carton, facing the packing list, the packing list marked with product name, specificcation model, quantity, date of dispatch.**

外包装为纸箱，贴装箱单、装箱单上注明产品名称、规格型号、数量、出货日期

- (3) **The product in the box must not rock.**

产品在箱内不晃动

### 8.2 Transportation

运输

**Allow for any way transportation, can't get wet and mechanical in jury.**

允许用任何方式运输，勿淋湿及机械性损伤

### 8.3 Storage

贮存

**The connector of packing finished should be in the ambient temperature between-10℃ to+40℃, Relative humidity≤80%. To store in storehouse does not have acidic, alkaline air and other corrosive gas in the ambient air.**

包装完毕的连接器应在环境温度为-10℃~+40℃，相对湿度≤80%，周围空气中没有酸性，碱性及其它腐蚀性气体的库房中贮存

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [hanxia](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-](#)  
[5028](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)