

## DIN-Signal coax m, solder/crimp 500hm



Part number	09 03 000 6162
Specification	DIN-Signal coax m, solder/crimp 500hm
HARTING eCatalogue	https://b2b.harting.com/09030006162

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Contacts
Series	DIN 41612
Type of contact	Coaxial contact
Description of the contact	Angled
Contacts for	DIN 41612 Type M invers

## Version

Termination method	PCB solder termination
Gender	Male contact for female connectors
Manufacturing process	Turned contacts

## **Technical characteristics**

Operating current	≤1.5 A
Rated voltage	250 V
Insulation resistance	>10 <sup>9</sup> Ω
Contact resistance	≤10 mΩ for inner contact die ≤3 mΩ for outer ferrule
Impedance	50 Ω
Limiting temperature	-55 +125 °C
Return loss	>30 dB @ 1 GHz >25 dB @ 2 GHz >22 dB @ 4 GHz >18 dB @ 6 GHz
Insertion force	≤10 N

Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Technical characteristics

Withdrawal force	≥1 N
Performance level	1
Mating cycles	≥500
Test voltage U <sub>r.m.s.</sub>	0.75 kV
Frequency	6 GHz

#### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side
Material (locking)	Copper alloy
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	339476a1-86ba-49e9-ab4b-cd336420d72a
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

### Specifications and approvals

Specifications	DIN 41626
Commercial data	
Packaging size	30
Net weight	2.1 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors

Page 2 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

 004.767
 608489050008049
 691327-1
 74670-0732
 74680-0340
 75880-0015
 76453-0014
 86093159ALF
 9732967801
 QLC260R

 120X10019X
 120X10089X
 122A10249X
 122A10669X
 122A11089X
 122A10089X
 122A10129X
 122A10349X

 122A13359X
 1377391-4
 DIN-048CPC-SR1-MH
 1393583-2
 1393726-7
 140X10129X
 143-1913-000
 143-1908-000
 1484472-1
 2110070-1

 2110070-2
 CBC20T00-008FDS5-0-1-002VR
 172699-5036
 2-1393557-4
 2-1437084-2
 CTJ720E01B-6141
 394506
 419-2080-402

 V42254B2202C968
 419-2086-201
 419-2087-002
 448657-1
 448847-3
 5-1393755-9
 02990000004
 054302
 043556
 09062483201750

 0850033067
 09031646555
 09061486901840
 0
 043556
 09062483201750