

## Han C module, crimp male



Part number	09 14 003 3001
Specification	Han C module, crimp male
HARTING eCatalogue	https://b2b.harting.com/09140033001

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Modules
Series	Han-Modular <sup>®</sup>
Type of module	Han <sup>®</sup> C module

#### Version

Termination method	Crimp termination
Gender	Male
Number of contacts	3
Details	Please order crimp contacts separately.

## **Technical characteristics**

Conductor cross-section	1.5 6 mm²
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated current acc. to UL	40 A
Rated voltage acc. to UL	600 V
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 +125 °C
Mating cycles	≥500

Page 1 / 2 | Creation date 2021-11-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### Material properties

Material (insert)Polycarbonate (PC)Colour (insert)RAL 7032 (pebble grey)Material flammability class acc. to UL 94V-0RoHScompliantRLV statuscompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNoREACH SUBStancesNoREACH SUBStancesNoREACH SUBStancesNo		
Material flammability class acc. to UL 94V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Material (insert)	Polycarbonate (PC)
RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Colour (insert)	RAL 7032 (pebble grey)
ELV status compliant   China RoHS e   REACH Annex XVII substances No   REACH ANNEX XIV substances No	Material flammability class acc. to UL 94	V-0
China RoHS e   REACH Annex XVII substances No   REACH ANNEX XIV substances No	RoHS	compliant
REACH Annex XVII substances No   REACH ANNEX XIV substances No	ELV status	compliant
REACH ANNEX XIV substances No	China RoHS	e
	REACH Annex XVII substances	No
REACH SVHC substances No	REACH ANNEX XIV substances	No
	REACH SVHC substances	No
California Proposition 65 substances No	California Proposition 65 substances	No

#### Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076

### Commercial data

Packaging size	2
Net weight	10.55 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440217 Module for industrial connectors (power/signals)

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2