

## Han Megabit insert female



| Part number        | 09 14 008 3116                      |
|--------------------|-------------------------------------|
| Specification      | Han Megabit insert female           |
| HARTING eCatalogue | https://b2b.harting.com/09140083116 |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category                  | Inserts   |
|---------------------------|---|
| Specification             | Han <sup>®</sup> Megabit insert<br>2x 4 contacts<br>2 cable entries   |
| Version                   |   |
| Termination method        | Crimp termination   |
| Gender                    | Female  |
| Number of contacts        | 8   |
| further contacts          | + shielding   |
| Details                   | Please order crimp contacts separately.<br>Please order adapter module separately.  |
| Details                   | Not suitable for hoods/housings low construction as well as Han-Modular <sup>®</sup> Eco, Han-Modular <sup>®</sup> Compact and Han-Modular <sup>®</sup> Twin. |
| Technical characteristics |   |
| Conductor cross-section   | 0.14 2.5 mm <sup>2</sup>  |
| Rated current             | 10 A  |

| Rated current                | 10 A                         |
|------------------------------|------------------------------|
| Rated voltage                | 50 V                         |
| Rated impulse voltage        | 0.8 kV                       |
| Pollution degree             | 3                            |
| Transmission characteristics | Cat. 5 Class D up to 100 MHz |

Page 1 / 2 | Creation date 2021-12-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## **Technical characteristics**

| Data rate                     | 10 Mbit/s<br>100 Mbit/s<br>1 Gbit/s<br>2.5 Gbit/s |
|-------------------------------|---|
| Contact resistance, shielding | ≤100 mΩ   |
| Limiting temperature          | -40 +85 °C  |
| Mating cycles                 | ≥500  |

#### Material properties

| Material (insert)                         | Polycarbonate (PC)           |
|---|------------------------------|
| Colour (insert)                           | RAL 7032 (pebble grey)       |
| Material (shielding)                      | Zinc die-cast, nickel-plated |
| Material flammability class acc. to UL 94 | V-0                          |
| RoHS                                      | compliant                    |
| ELV status                                | compliant                    |
| China RoHS                                | e                            |
| REACH Annex XVII substances               | No                           |
| REACH ANNEX XIV substances                | No                           |
| REACH SVHC substances                     | No                           |
| California Proposition 65 substances      | No                           |

## Specifications and approvals

| Specifications | EN 60664-1<br>IEC 61984                                    |
|----------------|--|
| Approvals      | DNV GL   |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

| Packaging size                 | 1  |
|--------------------------------|--|
| Net weight                     | 42 g   |
| Country of origin              | Germany  |
| European customs tariff number | 85389099   |
| eCl@ss                         | 27440218 Module for industrial connectors (data) |

Page 2 / 2 | Creation date 2021-12-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2