

Han DD module, crimp female



Part number	09 14 012 3102
Specification	Han DD module, crimp female
HARTING eCatalogue	https://b2b.harting.com/09140123102

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Modules
Series	Han-Modular [®]
Type of module	Han DD [®] module

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	12
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.14 2.5 mm²
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 +125 °C
Mating cycles	≥500
Mating cycles with other HMC components	≥10,000

Page 1 / 2 | Creation date 2021-12-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Material (insert)Polycarbonate (PC)Colour (insert)RAL 7032 (pebble grey)Material flammability class acc. to UL 94V-0RoHScompliantRLV statuscompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNoREACH SUBStancesNoREACH SUBStancesNoREACH SUBStancesNo		
Material flammability class acc. to UL 94V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Material (insert)	Polycarbonate (PC)
RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Colour (insert)	RAL 7032 (pebble grey)
ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Material flammability class acc. to UL 94	V-0
China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	RoHS	compliant
REACH Annex XVII substances No REACH ANNEX XIV substances No	ELV status	compliant
REACH ANNEX XIV substances No	China RoHS	e
	REACH Annex XVII substances	No
REACH SVHC substances No	REACH ANNEX XIV substances	No
	REACH SVHC substances	No
California Proposition 65 substances No	California Proposition 65 substances	No

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3

Commercial data

Packaging size	2
Net weight	9.35 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440217 Module for industrial connectors (power/signals)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2