

SEK CAB FLAT SH RND AWG28/7 34P 30,48m



Part number	09 18 034 7007
Specification	SEK CAB FLAT SH RND AWG28/7 34P 30,48m
HARTING eCatalogue	https://b2b.harting.com/09180347007

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)

Version

Cable length	30.48 m
Shielding	Shielded
Number of cores	34
Core structure	AWG 28/7

Technical characteristics

Impedance	100 Ω
Limiting temperature	-30 +75 °C unmoved -20 +75 °C moved
Conductor resistance @ 20 °C	≤216 Ω/km
Material properties	
Material (cable)	PVC
Colour (cable)	Grey
Dallo	a construction of the second se

RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2021-11-20 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Antimony trioxide

Specifications and approvals

Specifications	UL 1581 Sec. 1061 UL PLCC, CL2
CE	Yes
Commercial data	
Packaging size	1
Net weight	4,600 g
Country of origin	Germany
European customs tariff number	85444993
eCl@ss	27061801 Data and communication cable (copper)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

 F28-A25G
 F28-A34G
 F28-A36G
 FST-23A-15
 AYT1510-US
 171-37G
 C336514-500
 902220736002000
 902220736006000
 28100-0614

 9L28010-008-H300
 9L28014-008-H300
 F28-A24G
 F28-A60G
 25WDY00002
 28100-0571
 28100-0602
 28100-0650
 28100-0664
 336506

 100SF
 336512-300
 336518
 336537-CUT-LENGTH
 3447/10-100
 362514100MSF
 40WDY00005
 AYT51163
 336506-300
 C3302/16

 C374910
 3749/10-100
 375630
 3-971111-6
 1-1437356-3
 812504
 20WDY00001
 5-1437214-8
 3355/15
 40WBY0007
 3609/12
 5111196336

 607.5689.087
 607.5689.091
 3801/04
 8124/04
 3801/12
 3625/22100MSF
 902220736005000
 902220736004000
 C3811/10-100