

# Han 3A-HSI/P-DL-1Pg13,5-grey



| Part number        | 09 20 003 0120                      |
|--------------------|-------------------------------------|
| Specification      | Han 3A-HSI/P-DL-1Pg13,5-grey        |
| HARTING eCatalogue | https://b2b.harting.com/09200030120 |

Image is for illustration purposes only. Please refer to product description.

### Identification

| Category                 | Hoods/Housings        |
|--------------------------|-----------------------|
| Series of hoods/housings | Han A <sup>®</sup>    |
| Type of hood/housing     | Screw mounted housing |

### Version

| Size                 | 3 A   |
|----------------------|---|
| Cable entry          | 1x Pg 13.5  |
| Locking type         | Single locking lever                                |
| Field of application | Standard Hoods/housings for industrial applications |

### **Technical characteristics**

| Limiting temperature                   | -40 +125 °C  |
|--|--|
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                      |

### Material properties

| Material (hood/housing)                   | Polycarbonate (PC)                                     |
|---|--|
| Colour (hood/housing)                     | RAL 7032 (pebble grey)                                 |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |

Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 20 003 0120 Han 3A-HSI/P-DL-1Pg13,5-grey



### Material properties

| ELV status                           | compliant with exemption |
|--------------------------------------|--------------------------|
| China RoHS                           | 50                       |
| REACH Annex XVII substances          | No                       |
| REACH ANNEX XIV substances           | No                       |
| REACH SVHC substances                | Yes                      |
| REACH SVHC substances                | Lead                     |
| California Proposition 65 substances | Yes                      |
| California Proposition 65 substances | Lead                     |

## Specifications and approvals

| Approvals       | DNV GL   |
|-----------------|--|
| UL / CSA        | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE              | Yes  |
| Commercial data |  |

# Packaging size10Net weight16.94 gCountry of originRomaniaEuropean customs tariff number85389099eCl@ss27440202 Shell for industrial connectors

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2