


# Han EE 18 Pos. Insert Male Crimp



Part number	09 32 018 3001
Specification	Han EE 18 Pos. Insert Male Crimp
HARTING eCatalogue	https://b2b.harting.com/09320183001

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Inserts
Series	Han <sup>®</sup> EE

## Version

Termination method	Crimp termination
Gender	Male
Size	10 B
Number of contacts	18
PE contact	Yes
Details	Please order crimp contacts separately.

# Technical characteristics

Conductor cross-section	0.14 4 mm²
Conductor cross-section	AWG 26 AWG 12
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Rated voltage acc. to CSA	600 V
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 +125 °C

Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### Technical characteristics

Mating cycles	≥500
Material answertige	
Material properties	
Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

### Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 UL 2237 PVVA2.E318390 CSA-C22.2 No. 182.3 PVVA8.E318390

## Commercial data

Packaging size	1
Net weight	50.26 g
Country of origin	Romania
European customs tariff number	85389099
eCl@ss	27440205 Contact insert for industrial connectors

Page 2 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 73000005059 73000005642 765-15-0080A 765-16-0080B 829992-1 902-77-02113 129-1J AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102 9300480317 SBS50BRN#6 29131 29652 1646905-1 1648320-1 1648582-1 1650195-2