


USB 3.0 IP20 cable 0,5m; 2x type A 1:1



Part number	09 45 145 2930
Specification	USB 3.0 IP20 cable 0,5m; 2x type A 1:1
HARTING eCatalogue	https://b2b.harting.com/09451452930

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	har-port
Element	Service interfaces
Specification	USB 3.0
Connector 1	IP20 USB 3.0 Type A
Connector 2	IP20 USB 3.0 Type A

Version

Cable length	0.5 m
Shielding	Fully shielded, 360° shielding contact
Core structure	4x AWG 28/7
	2x AWG 28/7
	2x AWG 24/7
Connection type	Type A connector - type A connector
Fixing	Screwable in cover plates

Technical characteristics

Ambient temperature	-25 +70 °C
Mating cycles	≥1,500
Degree of protection acc. to IEC 60529	IP20
Cable diameter	5.8 mm



Material properties

Polyamide (PA)
Black
PVC
Black
compliant
compliant
е
No
No
No

Specifications and approvals

Approvals DNV GL

Commercial data	
Packaging size	1
Net weight	41.7 g
Country of origin	Malaysia
European customs tariff number	85444290
eCl@ss	27060304 Appliance cord (data cable)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Cables / IEEE 1394 Cables category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

68768-0173 FNY-W6003-01 88764-0800 148700-1 17-200621 17-250051P 954 17-200261 AC102012-1 AC102012-2 FTP-629Y601 451345-15 45-1358-15 45-1363-15 IP-USB1(C10)S-RW CABLE/RTP/USB/DT 45-1351-15 45-1357-15 45-1433-1 687680278

USBFTVX2SA2N03A USBFTV2SA2N03A USBFTV2SA2N05A MDM9PH004B MDM9PH004P FTP-629Y401 FTP-628Y302 FTP628Y402 CSMNB9MF-5 FNY-W6022 UA-30AMF-SD7B03 UA-30AMFM-SL7B03 USBAPSCC7202A UES-1001A160 UES-1003A160

USBFTVX7SA2N20A USBFTV2PEMSA2N10A FTP-629Y602 USBCAMCM100 USB A/F*2 to 2.54 2*5P-SH L=400mm 68784-0075

USB-29 19800-010500-200-RS 103-1092-BL-F0050 103-1020-BL-00100 103-1092-BL-F0200 103-1092-BL-F0100 105-1092-BL-00300

105-1092-BL-00200 105-1031-BL-00200