

T1 Industrial plug SL-C IP20



Part number	09 45 181 2800 XL
Specification	T1 Industrial plug SL-C IP20
HARTING eCatalogue	https://b2b.harting.com/09451812800XL

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	HARTING T1 Industrial
Element	Cable connector
Specification	Straight

Version

Termination method	Crimp termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	2
further contacts	+ shielding
Details	Please order crimp contacts separately.
Pack contents	Packaging with 100 pieces

Technical characteristics

Conductor cross-section	0.08 0.32 mm² Stranded
Conductor cross-section	AWG 28/7 AWG 22/7 Stranded
Wire outer diameter	≤1.8 mm
Rated current	4 A
Rated voltage	60 V DC
Transmission characteristics	600 MHz Bandwidth
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s
Contact resistance	≤20 mΩ



Technical characteristics

Shielding resistance	≤100 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥1,000
Degree of protection acc. to IEC 60529	IP20
Cable diameter	4.5 6 mm
Test voltage U _{DC}	1 kV (contact-contact) 2.25 kV (contact-ground)

Material properties

RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

	IEC 63171-6
	IEEE 802.3bu (remote power supply over PoDL = Power over Data Line)
Specifications	IEEE 802.3cg (10BASE-T1)
	IEEE 802.3bw (100BASE-T1)
	IEEE 802.3bp (1000BASE-T1)

Commercial data

Packaging size	100
Net weight	3.5 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27460202 PCB connector (conductor connection)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHJ-4P4C-1-V-4 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L 155302-001 AX100653