

## Set Han3A M plug 2x LC duplex SM GOF



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 57 407 0002 000  |
| Specification      | Set Han3A M plug 2x LC duplex SM GOF  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09574070002000">https://b2b.harting.com/09574070002000</a> |

### Identification

|                             |                 |
|-----------------------------|-----------------|
| Category                    | Connectors      |
| Series                      | LC duplex       |
| Element                     | Cable connector |
| Type of contact             | LC contact      |
| Description of the contact  | Singlemode      |
| Type of hood/housing        | Hood            |
| Description of hood/housing | Straight        |

### Version

|                    |                      |
|--------------------|----------------------|
| Size               | Han <sup>®</sup> 3 A |
| Number of contacts | 4                    |

### Technical characteristics

|  |                |
|--|----------------|
| Limiting temperature                   | -40 ... +70 °C |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67   |

### Material properties

|                         |                          |
|-------------------------|--------------------------|
| Material (hood/housing) | Zinc die-cast            |
| Surface (hood/housing)  | Powder-coated            |
| Colour (hood/housing)   | Black                    |
| RoHS                    | compliant with exemption |



Pushing Performance

## Material properties

|                                      |  |
|--------------------------------------|--|
| RoHS exemptions                      | 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight<br>6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption   |
| China RoHS                           | 50   |
| REACH Annex XVII substances          | No   |
| REACH ANNEX XIV substances           | No   |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | Lead   |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Nickel<br>Lead<br>Antimony trioxide<br>Naphthalene   |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |                                       |
|--------------------------------|---------------------------------------|
| Packaging size                 | 1                                     |
| Net weight                     | 157.5 g                               |
| Country of origin              | Germany                               |
| European customs tariff number | 85366990                              |
| eCl@ss                         | 27440101 Rectangular connectors (set) |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fibre Optic Connectors](#) category:*

*Click to view products by [HARTING](#) manufacturer:*

Other Similar products are found below :

[0004700001](#) [6100-R](#) [6313](#) [F709034706](#) [F709722200](#) [F709730000](#) [F718183204](#) [F727403500](#) [8119](#) [9440F20-27S-190](#) [944-120-6001](#)  
[9441F10SL-3P](#) [9441F10SL-3S](#) [9444W28-21S](#) [9444W36-10S](#) [9446F10SL-4S](#) [9446W20-16S](#) [953-101-5310-P](#) [954-101-57202B](#) [A0270169](#)  
[12-9122](#) [12-5702](#) [AX101713](#) [AX102420](#) [AX103923](#) [AX104024](#) [AX104193](#) [AX104230](#) [AX104498](#) [AX104562](#) [AX105203-B25](#)  
[AX105205-S1](#) [181-011-126](#) [181-011-S](#) [181-057-126](#) [NKSOPBUY](#) [20500002116](#) [2064996-1](#) [20800001065](#) [2170](#) [9132](#) [2612](#) [2620](#) [9291](#)  
[9440F16-10S](#) [9440F20-18S](#) [9440W18-1S](#) [9442W14S-10P](#) [9446F16-10S-190](#) [953-106-50231](#)