

DSUB SV FE TWW STR 25P AU3



Part number	09 67 025 4707
Specification	DSUB SV FE TWW STR 25P AU3
HARTING eCatalogue	https://b2b.harting.com/09670254707

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	D-Sub
Identification	Standard
Element	Connector
Description of the contact	Turned Straight

Version

Termination method	Wrap termination
Gender	Female
Size	D-Sub 3
Connection type	PCB to cable
Number of contacts	25
Termination length	13.65 mm
Locking type	Fixing flange with feed through hole \emptyset 3.1 mm
Pack contents	Carton

Technical characteristics

Distance between rows	2.54 mm
Rated current	7.5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	>10 ¹⁰ Ω

Page 1 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 67 025 4707 DSUB SV FE TWW STR 25P AU3



Technical characteristics

Contact resistance	≤10 mΩ
Limiting temperature	-55 +125 °C
Performance level	3
Mating cycles	≥50
Test voltage U _{r.m.s.}	1 kV
Isolation group	Illa (175 ≤ CTI < 400)
Hot plugging	No

Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Plated steel
Colour (insert)	White
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	ecef7555-f643-4ceb-a337-fc54762297f1
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Antimony trioxide

Specifications and approvals

UL 1977 ECBT2.E102079	
	DIN 41652 UL 1977 ECBT2.E102079

Commercial data

Packaging size

25

Page 2 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 67 025 4707 DSUB SV FE TWW STR 25P AU3



Commercial data

Net weight

Country of origin

14.9 g Germany

European customs tariff number

eCl@ss

85366990 27440214 D-Sub coupler

Page 3 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

 56F706-005-LI
 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000

 012-9507-034
 012-9507-114
 020745-0008
 609-25P
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 CT6N10SL-4SSA34
 M83513/01-FC
 M83723/76W24619 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X

 6STD09SCT99S40X
 6STD15PCT99S40X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171