

DSUB SV MA TSDP STR 37P AU2



| Part number | 09 67 037 5655 |
|--------------------|-------------------------------------|
| Specification | DSUB SV MA TSDP STR 37P AU2 |
| HARTING eCatalogue | https://b2b.harting.com/09670375655 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|--------------------|
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Turned Straight |

Version

| Termination method | Wave soldering termination |
|--------------------|--|
| Gender | Male |
| Size | D-Sub 4 |
| Connection type | Motherboard to daughtercard Mezzanine |
| Number of contacts | 27 |
| Number of contacts | 37 |
| Termination length | 5.8 mm |
| | |
| Termination length | 5.8 mm |

Technical characteristics

| Distance between rows | 2.54 mm |
|-----------------------|---------|
| Flange height | 6.5 mm |
| Rated current | 7.5 A |
| Clearance distance | ≥1 mm |

Page 1 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 67 037 5655 DSUB SV MA TSDP STR 37P AU2



Technical characteristics

| Creepage distance | ≥1 mm |
|----------------------------------|-----------------------------|
| Insulation resistance | >10 ¹⁰ Ω |
| Contact resistance | ≤10 mΩ |
| Limiting temperature | -55 +125 °C |
| Performance level | 2 acc. to CECC 75301-802 |
| Mating cycles | ≥250 |
| Test voltage U _{r.m.s.} | 1 kV |
| Isolation group | IIIa (175 ≤ CTI < 400) |
| Hot plugging | No |

Material properties

| Material (insert) | Thermoplastic resin, glass-fibre filled (PBTP) Plated steel |
|---|--|
| Colour (insert) | White |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | ecef7555-f643-4ceb-a337-fc54762297f1 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Lead Antimony trioxide |
| | |

Specifications and approvals

Specifications

DIN 41652

Page 2 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 67 037 5655 DSUB SV MA TSDP STR 37P AU2



Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E102079 |
|--------------------------------|------------------------|
| Commercial data | |
| Packaging size | 50 |
| Net weight | 1 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27440214 D-Sub coupler |

Page 3 / 3 | Creation date 2021-10-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

 56F706-005-LI
 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000

 012-9507-034
 012-9507-114
 020745-0008
 609-25P
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 CT6N10SL-4SSA34
 M83513/01-FC
 M83723/76W24619 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X

 6STD09SCT99S40X
 6STD15PCT99S40X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171