

## Han® S-HBM w. MC M8-black



Part number	09 93 001 0301
Specification	Han® S-HBM w. MC M8-black
HARTING eCatalogue	https://b2b.harting.com/09930010301

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> S
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	incl. male contact with M8 bolt termination
Version	
Number of contacts	1
Locking type	Single locking lever
Field of application	Energy Storage Systems
Technical characteristics	
Rated current	200 A
Rated voltage	1,500 V
Rated impulse voltage	8 kV

Rated impulse voltage	0 KV
Pollution degree	2
Insulation resistance	>10 <sup>8</sup> Ω
Contact resistance	≤0.3 mΩ
Limiting temperature	-40 +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP40 mated condition IP20 unmated condition (1500 V DC; 1000 V AC)

Page 1 / 2 | Creation date 2022-01-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 93 001 0301 Han® S-HBM w. MC M8-black



### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
ELV status China RoHS	compliant e
China RoHS	e
China RoHS REACH Annex XVII substances	e Not contained

### Specifications and approvals

Specifications	EN 60664-1
	IEC 61984
	UL 1973
	UL 4128
	UL 9540
	UL 1977

#### Commercial data

Packaging size	1
Net weight	34 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors

Page 2 / 2 | Creation date 2022-01-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below :

 647757-1
 6643411-1
 6646058-2
 6646137-1
 6646138-1
 6646608-1
 6646786-1
 6646940-1
 6651091-1
 6651525-1
 6651529-1
 6651788-1

 696475-1
 702-32-01109
 703-25-02205
 73000005059
 73000005642
 73080254296
 73080255059
 73080965046
 765-15-0080A

 765-16-0080B
 765-18-0080D
 902-77-02113
 PS00/A0620/6300
 1221200000
 129-1J
 1409400
 E6374G1
 e6389g2
 157-43GW8
 MS3117 

 14AC
 1643543-1
 1650540-1
 1651811-2
 1766260-1
 1766282-1
 1766966-1
 1791340000
 NLDFT-3-BL-L-S120-M40A
 NLDFT-N-W-L 

 C240-M40B
 1926015-1
 NLS-N-W-C240-M40B
 2-1589900-8
 2199314-1
 KA8102
 9300480317
 29131
 294-0091-01100
 296-0040-01100