

Han® S 120 HSI w. MC M6 blue



Part number	09 93 001 1108
Specification	Han® S 120 HSI w. MC M6 blue
HARTING eCatalogue	https://b2b.harting.com/09930011108

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series	Han [®] S
Identification	Han [®] S 120
Type of hood/housing	Screw mounted housing
Description of hood/housing	incl. male contact with M6 bolt termination

Version

Number of contacts	1
Locking type	Single locking lever
Field of application	Energy Storage Systems

Technical characteristics

Rated current	120 A
Rated voltage	1,500 V
Rated impulse voltage	8 kV
Pollution degree	2
Insulation resistance	>10 ⁸ Ω
Contact resistance	≤0.3 mΩ
Tightening torque	4 Nm
Wrench size	9
Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Number of relockings	≥500

Page 1 / 3 | Creation date 2022-12-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

Degree of protection acc. to IEC 60529

IP40 mated condition
IP20 unmated condition (1500 V DC; 1000 V AC)

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	RAL 5015 (sky blue)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

	IEC 60664-1
	EN 45545-2 Fire protection on railway vehicles
	IEC 61984
Specifications	UL 1973
	UL 4128
	UL 9540
	UL 1977
CE	Yes

Commercial data

Packaging size	1
Net weight	14.55 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140183391

Product data sheet 09 93 001 1108 Han® S 120 HSI w. MC M6 blue



Commercial data

eCl@ss

27440202 Shell for industrial connectors

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

6646058-2 6646137-1 6646138-1 6646940-1 6651091-1 6651525-1 6651529-1 696475-1 702-32-01109 73080255059 73080965046

7310205040001 765-16-0080B 765-18-0080D 902-77-02113 PS00/A0620/6300 AN0024023 154-42B7WM250 MS3117-14AC 1643543-1

1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B 1926015-1 NLS-3-BL-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 2-1589900-8 9300480317 294-0091-01100 296-0040-01100 1-6609148-0 A32595-0049 1766249-1 19000005132

1926016-1 1-966831-8 AN0024202 AN0264023 279-0841-10100A 281-0334-00100A RMSB4 419-2083-301 LCDX4/0-14B-X 075-8519-001 078238-1613 07.470.3256.0 09000005288 09140240311